

Safety Data Sheet according to WHS Regulations

Printing date 25.05.2017 Revision: 25.05.2017

1 Identification

Product Name: SOUDAL TRADE ROOF & GUTTER SILICONE

Other Means of Identification: Mixture

Part Number: 49181

Recommended Use of the Chemical and Restriction on Use: Sealant

Details of Manufacturer or Importer:

Soudal Australia Pty Ltd Unit 1, 29 Prince William Drive

Seven Hills NSW 2147

Phone Number: 02 8678 7449

Emergency telephone number: 1300 507 011

2 Hazard(s) Identification

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)



Carcinogenicity 2 H351 Suspected of causing cancer.

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



Serious Eye Damage/Irritation 2A H319 Causes serious eye irritation.

Skin Sensitisation 1 H317 May cause an allergic skin reaction.

Signal Word Danger

Hazard Statements

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H304 May be fatal if swallowed and enters airways.

Precautionary Statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

according to WHS Regulations

Printing date 25.05.2017 Revision: 25.05.2017

Product Name: SOUDAL TRADE ROOF & GUTTER SILICONE

(Contd. of page 1)

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national regulations.

3 Composition and Information on Ingredients

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:		
	Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	>10%
	♦ Aspiration Hazard 1, H304	
96-29-7	2-butanone oxime	1-<3%
	♦ Carcinogenicity 2, H351; ♦ Serious Eye Damage/Irritation 1, H318; ♦ Acute Toxicity (Dermal) 4, H312; Skin Sensitisation 1, H317; Flammable Liquids 4, H227	′
1760-24-3	1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-	0.1-<1%
	Serious Eye Damage/Irritation 1, H318; Skin Corrosion/Irritation 2, H315; Skin Sensitisation 1, H317	

4 First Aid Measures

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention if symptoms persist.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Never give anything by mouth to an unconscious person. Seek medical attention.

Symptoms Caused by Exposure:

Skin Contact: May cause slight skin irritation. Eye Contact: Causes serious eye irritation.

Ingestion: May cause nausea.

5 Fire Fighting Measures

Suitable Extinguishing Media: Water spray, polyvalent foam, dry chemical powder and carbon dioxide.

Specific Hazards Arising from the Chemical:

In case of fire carbon monoxide, carbon dioxide and small quantities of nitrous vapours may be released. Not easily combustible.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

(Contd. on page 3)

according to WHS Regulations

Printing date 25.05.2017 Revision: 25.05.2017

Product Name: SOUDAL TRADE ROOF & GUTTER SILICONE

(Contd. of page 2)

6 Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved respiratory protection and full protective clothing. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so. Collect the spill only if it is in a dry state. Clean contaminated surfaces with a soap solution.

7 Handling and Storage

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only outdoors or in a well-ventilated area.

Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use. Protect from heat, sparks, open flames and other sources of ignition.

8 Exposure controls and personal protection

Exposure Standards:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Engineering Controls: Ensure adequate ventilation of the working area.

Respiratory Protection:

Use an approved vapour respirator under conditions where exposure to the substance is apparent (e.g. generation of high concentrations of mist or vapour, inadequate ventilation, development of respiratory tract irritation) and engineering controls are not feasible. See Australian Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

PVC, PVA, nitrile, neoprene, rubber or vinyl gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Safety glasses with top and side shields or goggles. See Australian/New Zealand Standards AS/NZS 1337 for more information.

(Contd. on page 4)

according to WHS Regulations

Printing date 25.05.2017 Revision: 25.05.2017

Product Name: SOUDAL TRADE ROOF & GUTTER SILICONE

(Contd. of page 3)

9 Physical and Chemical Properties

Appearance:

Form: Paste

Colour: Variable in colour, depending on the composition

Odour: Characteristic

Odour Threshold:

pH-Value:

Melting point/freezing point:
Initial Boiling Point/Boiling Range:
Plash Point:

Flammability:
Auto-ignition Temperature:

No information available

Explosion Limits:

Lower: No information available Upper: No information available Vapour Pressure: No information available

Density: 1180 kg/m³

Relative Density: 1.2

Vapour Density:No information availableEvaporation Rate:No information available

Solubility in Water: Insoluble VOC: <2 %

10 Stability and Reactivity

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: Heat, sparks, open flames and other sources of ignition.

Incompatible Materials: No information available

Hazardous Decomposition Products:

Carbon monoxide, carbon dioxide and small quantities of nitrous vapours.

11 Toxicological Information

Toxicity:

LD ₅₀ /LC ₅₀ Values Relevant for Classification:				
96-29-7 2-butanone oxime				
Oral	LD ₅₀	2326 mg/kg (rat) (male)		
Dermal	LD ₅₀	>2000 mg/kg (rat)		
	LD ₅₀ /24h	>1000 mg/kg (rabbit) (male/female)		
Inhalation	LC₅₀/4 h	>4.83 mg/l (rat) (male/female)		
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics				
Oral	LD ₅₀	>5000 mg/kg (rat) (male/female)		
Dermal	LD ₅₀ /24 h	>3160 mg/kg (rabbit) (male/female)		
Inhalation	LC₅₀/4 h	>5266 mg/l (rat) (male/female)		

(Contd. on page 5)

according to WHS Regulations

Printing date 25.05.2017 Revision: 25.05.2017

Product Name: SOUDAL TRADE ROOF & GUTTER SILICONE

(Contd. of page 4)

1760-24-3	1760-24-3 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-		
Oral	LD ₅₀	2413 mg/kg (rat) (male/female)	
		7684 mg/kg (rat) (male)	
Dermal	LD ₅₀ /24 h	>2000 mg/kg (rabbit) (male/female)	
		16480 mg/kg (rabbit) (male/female)	
Inhalation	LC₅₀/4 h	1.49-2.44 mg/l (rat) (male/female)	

Acute Health Effects

Inhalation: No adverse health effects expected.

Skin: May cause slight skin irritation. **Eye:** Causes serious eye irritation. **Ingestion:** May cause nausea.

Skin Corrosion / Irritation: Based on classification principles, the classification criteria are not met.

Serious Eye Damage / Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitisation: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity:

This product does NOT contain any IARC listed chemicals.

Suspected of causing cancer.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Single Exposure:

Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Chronic Health Effects: Continuous or repeated contact may cause skin rash/ inflammation.

Existing Conditions Aggravated by Exposure: No information available

12 Ecological Information

Ecotoxicity:

Aquatic toxicity:		
1760-24-3 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-		
EC₀/48 h	<63 mg/l (daphnia) (OECD 202)	
EC₅₀/16 h	67 mg/l (pseudomonas putida)	
EC₅₀/48 h	81 mg/l (daphnia)	
	90 mg/l (daphnia) (OECD 202)	
EC₅₀/72 h	5.5 mg/l (selenastrum capricornutum)	
LC₅₀/96 h	213 mg/l (fish) (EPA 660/3-75/009)	
	597 mg/l (fish)	
LC₅₀/14 day	LC ₅₀ /14 day >1000 mg/kg soil (worms)	
96-29-7 2-butanone oxime		
EC₅₀/48 h	201 mg/l (daphnia)	

(Contd. on page 6)

according to WHS Regulations

Printing date 25.05.2017 Revision: 25.05.2017

Product Name: SOUDAL TRADE ROOF & GUTTER SILICONE

(Contd. of page 5)

EC₅₀/72 h	11.8 mg/l (algae)	
LC₅₀/96 h	>100 mg/l (fish)	
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics		
EC₅₀/3 h	>100 mg/l (activated sludge inhibition)	
LC ₅₀ /48 h	>3193 mg/l (crustacea)	
LC₅₀/96 h	>1028 mg/l (fish)	

Persistence and Degradability: Contains non readily biodegradable component.

Bioaccumulative Potential: Bioaccumulation is not expected to occur.

Mobility in Soil: Components adsorb into the soil.

Other adverse effects:

None of the known components is included in the list of fluorinated greenhouse gases.

Not classified as dangerous for the ozone layer.

13 Disposal considerations

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14 Transport information

UN Number Not regulated
 Proper Shipping Name Not regulated
 Dangerous Goods Class Not regulated
 Packing Group: Not regulated
 Marine pollutant: No

15 Regulatory information

Australian Inventory of Chemical Substances:

	•
96-29-7	2-butanone oxime
1760-24-3	1,2-Ethanediamine, N-[3-(trimethoxysilyI)propyI]-

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:

Not a scheduled poison.

16 Other information

Date of Preparation or Last Revision: 25.05.2017

Prepared by: MSDS.COM.AU Pty Ltd www.msds.com.au

Abbreviations and acronyms:

GHS: Globally Harmonised System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds LC₅₀: Lethal concentration, 50 percent

LD₅o: Lethal dose, 50 percent IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Flammable Liquids 4: Flammable liquids – Category 4

Safety Data Sheet according to WHS Regulations

Printing date 25.05.2017 Revision: 25.05.2017

Product Name: SOUDAL TRADE ROOF & GUTTER SILICONE

(Contd. of page 6)

Acute Toxicity (Dermal) 4: Acute toxicity – Category 4
Skin Corrosion/Irritation 2: Skin corrosion/irritation – Category 2
Serious Eye Damage/Irritation 1: Serious eye damage/eye irritation – Category 1
Serious Eye Damage/Irritation 2A: Serious eye damage/eye irritation – Category 2A
Skin Sensitisation 1: Skin sensitisation, Hazard Category 1
Carcinogenicity 2: Carcinogenicity – Category 2
Aspiration Hazard 1: Aspiration hazard – Category 1

Disclaimer

This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - February 2016"

The information contained in this material safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Soudal Australia Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.