



BOSTIK 5612

NON SKINNING BUTYL MASTIC SEALANT

8 December 2017

YOUR SMART ADVANTAGES

- Excellent UV light resistance in glazing applications.
- Tenacious adhesion to nearly all surfaces
- Good service temperature range (-35°C to 65°C)
- Indefinite ageing characteristics
- Cost effective

DESCRIPTION

Bostik Non Skinning Mastic 5612 is specifically formulated as a bedding or gasket style sealant. It remains in a soft plastic state providing a dust proof, weatherproof and flexible seal in a variety of construction and manufacturing materials.

USES

Cool room wall component sealing.
Sea container metal to metal lap joints
Air conditioning flange joint sealing
Glazing seal
Bedding or internal sealing on construction fitting such as aluminum windows or flashing.

PRECAUTION

This product is **not recommended** in the following applications:

- For concrete, block or brick work joint sealing as the product does not set or skin and the permanent tacky surface will attract air borne contaminants.
- For medium to high movement joints.
- For joints which are exposed to mechanical or physical abuse.
- For continuous immersion.

CLEAN UP

Mineral Turps is recommended for use when cleaning up 5612.

P.A.T.S (Pretested Adhesion to Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied.

This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

HEALTH & SAFETY

For detailed information refer to the products Safety Data Sheet (SDS).

STORAGE & TRANSPORTATION

Store in a cool area, under cover between 5°C to 25°C.

SHELF LIFE

A minimum of 2 years shelf life is expected if stored as above in unopened containers.

PRODUCT CHARACTERISTICS

Product code	
450 g Ctg	
Bostik 5612 Sealer White	30804526

BOSTIK 5612 NON SKINNING BUTYL MASTIC SEALANT

For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com/au