



A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road
St Marys NSW 2760
Australia

Ph: 1300 738 250 (Australia)
Ph: +61 2 9833 9766 (International)
Fax: 02 9623 3670

sales@chemtools.com.au
www.chemtools.com.au

TECHNICAL DATA SHEET

FEBRUARY 2015

PRODUCT NAME

R25 All Purpose Spray Adhesive

PRODUCT RANGE

Part Number
CT-R25-400

Available Size
400g Aerosol



Refer to SDS for product safety guidelines

R25 All Purpose Spray Adhesive

Chemtools® R25 All Purpose Spray Adhesive is an advanced formula mist spray adhesive. This unique product utilizes an advanced rubber system to create a product versatile enough for everything from light to heavy duty jobs. Applications for this product include bonding most metals, felt, cork, fabric, plastics, paper, corrugated cardboard, wood, and a variety of other materials.

This product has a conveniently long open time to allow for repositioning and adjustment when affixing surfaces to be bonded. Another feature is a moderate flow rate spray valve to provide over-spray control in a mist adhesive.

FEATURES AND BENEFITS:

- Bonds a variety of materials
- Long open time
- Non-Staining
- Rapid tack formula provides speedy bonding

APPLICATION:

- Home improvements and repair
- Picture framing and scrapbooking
- Bonding fabrics
- General decorating, crafts and other projects

DIRECTIONS FOR USE:

- Ensure surfaces to be bonded are clean, dry and free from grease, oil dust and other foreign materials.
- Shake can well before use.
- Spray evenly onto the surface to be bonded. For higher bond strength apply to both surfaces.
- Allow 3 minutes contact time for the adhesive to become tacky.
- Push surfaces together and allow to dry.
- If surfaces are prone to separation, hold or clamp in position until dry.
- While Adhesive Spray will provide an initial bond, full strength will be achieved in 24 hours.
- After use, turn can upside down, depress spray nozzle and spray to clear the nozzle and prevent blockage.

Note: Wherever possible pre-test surfaces for compatibility and bond strength prior to full scale application. Unsuitable for use on solvent sensitive plastics and polystyrene.

PROPERTIES:

Appearance	Aerosol
Pack Size	12 x 400g Aerosols
Colour	Off-White to Pale yellow
Odour	Solvent
Active Solids	17%
Adhesive Type	Synthetic rubber
VOC Content	491g/L
Propellant	Hydrocarbon

STORAGE:

Store in a cool, dry place, in tightly closed original containers, at a room temperature of between 5°C to 40°C. Do not place in direct sunlight or near any heat source. Do not return any used material to its original container.

PRECAUTIONS:

This product is capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the material.

WARRANTY:

All products purchased from or supplied by Chemtools® are subject to terms and conditions set out in the contract. Chemtools® warrants only that its products meet the specifications designated as such herein, or in other publications. All other information supplied by Chemtools® is considered accurate, but is furnished upon the express condition. The customer shall make its own assessment to determine the products suitability for a particular purpose. Chemtools® makes no other warranty, either expressed or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or products will not infringe any patent.