

AF-Series – ABAC™ Pumps

Belt Drive – 240 Volt

Built in Australia.

Features the world famous ABAC pump.

Built for professional applications,
not just a price.

- ◆ ABAC pump.
- ◆ Rated to AS4637.
- ◆ Cast iron cylinder.
- ◆ TECO motor with overload protection.
- ◆ Supported by TECO National Service Network.
- ◆ Capacitor start/Capacitor run.
- ◆ Filter/regulator included.
- ◆ Condor German made pressure switch.
- ◆ Adjustable cut in/cut out differential.
- ◆ 60 Litre powder coated tank.
- ◆ Tank meets Australian Standard AS1210.
- ◆ Light weight for portability.
- ◆ Removable handle and axle.
- ◆ Fan forced cooling.
- ◆ Warranty.
 - 5 years on pump.
 - 5 years on tank.
 - 1 year on motor and fittings.
- ◆ Dual control option available for all models.**



AF 12



AF 16/L

Dimensions (mm)	Length	Width	Height	Weight (kg)
AF 12	940	335	700	61
AF 16	940	335	740	66
AF 16L	1,450	400	840	105
AF 430	1,500	500	920	162

* Dimensions exclude wheels and handle

Product Code	Displacement CFM	L/min	Free Air Delivery CFM	L/min	Motor Hp	Tank Litres	Power Supply	Pump Model	Max. Pressure	Cylinders
AF 12	11.7	331	8.4	238	2.2	60	10A	B2800	130psi	Twin
AF 16	16.4	464	12.3	348	3.0	60	15A	B3800	130psi	Twin
AF 16/L	16.4	464	12.3	348	3.0	125	15A	B3800	130psi	Twin
AF 430	17.3	489	15.1	430	5.0	155	20A	A49B	160psi	Twin

** Dual control allows for constant run option if power is supplied by marginally sized generator or in an area with bad 240 volt power
Refer to website for more information

CFM x 28.3 = Litres per minute
Displacement & FAD calculated at 100psi.
3.0Hp motors must only be used with 15A power outlet.
Specifications/configuration may change at any time without notice.

E&OE V9.18

For improved air quality please consider our
Refrigerated Dryers and Filters.

www.mcmillanair.com.au