



A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road
St Marys NSW 2760
Australia

Ph: 1300 738 250 (Australia)
Ph: +61 2 9833 9766 (International)
Fax: 02 9623 3670

sales@chemtools.com.au
www.chemtools.com.au

TECHNICAL DATA SHEET

OCTOBER 2014

PRODUCT NAME

CT-ESF Easy Start Engine Starting Fluid

PRODUCT RANGE

Part Number	Available Size
CT-ESF-300	300g Aerosol



Refer to MSDS for product safety guidelines

CT-ESF Easy Start Engine Starting Fluid

Chemtools® Easy Start Engine Starting Fluid Spray is formulated for use on all combustion engines. The unique blend of active ingredients enables reliable cold starting. CSS will work in damp weather, after long periods of downtime of engines, and at low temperatures. It is compatible with both petrol and diesel engines.

FEATURES AND BENEFITS:

- Self-healing properties
- Long term corrosion protection outdoors - up to 6 months
- Convenient aerosol spray
- Leaves clear film that can be easily removed

APPLICATIONS:

- | | | |
|---------------------|--------------------|-----------------------------|
| - Farming Equipment | - Motorcycles | - Marine Engines |
| - Mowers | - Garden Equipment | - Motor Vehicles and Trucks |
| - Mining Equipment | | |

PROPERTIES:

Appearance	Clear/Colourless
Odour	Ether - Solvent
Ignition Temperature	> 200°C
Propellant	CO ₂
Shelf Life	Up to 1 year from date of manufacture

DIRECTIONS FOR USE:

Shake well before use. For petrol engines: spray into the carburetor or vacuum hose. For diesel engines: spray into the air inlet. Spray moderately to avoid excessive fluid and uncontrolled running of the engine.

PRECAUTIONS:

This product is capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the material.

WARRANTY:

All products purchased from or supplied by Chemtools® are subject to terms and conditions set out in the contract. Chemtools® warrants only that its products meet the specifications designated as such herein, or in other publications. All other information supplied by Chemtools® is considered accurate, but is furnished upon the express condition. The customer shall make its own assessment to determine the products suitability for a particular purpose. Chemtools® makes no other warranty, either expressed or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or products will not infringe any patent.