



# PENRITE



85% REDUCTION  
IN LANDFILL  
WASTE

## EXTREME PRESSURE GREASE

Last updated: 29/06/2021 11:38 am

PRODUCT CODE	PACK SIZE	CARTON QTY
EPGR00045	450g	6
EPGR0005	500g	6
EPGR0025	2.5Kg	6
EPGR020	20Kg	
EPGR055	55Kg	
EPGR180	180Kg	



### PRODUCT BENEFITS

**Extreme Pressure Grease** is an NLGI No 2, red coloured, general purpose grease manufactured from high quality base oils and uses a lithium soap base.

### APPLICATION

**Extreme Pressure Grease** is suitable for use in all general grease applications in automotive and industrial service. This includes plain bearings, slow speed wheel and anti-friction bearings, chassis grease, general plant lubrication and agricultural and construction equipment lubrication.

**NOTE:** For high speed, high temperature applications, including wheel bearings of vehicles fitted with disc brakes, [Penrite High Temperature Wheel Bearing Grease](#) should be used.

### PRODUCT BENEFITS

- Extreme pressure performance for protection against shock loadings
- Resists water wash out.
- Protects against rust and corrosion.
- Long service life.
- Tackiness additive helps grease stay in place.

### PRODUCT PERFORMANCE LEVELS

- DIN 51502
- ISO 6743: KP2K-30
- NLGI 2

### TYPICAL DATA

Colour	Red
NLGI Grade	2
Soap Type	Lithium
Density at 15°C, kg/L	0.9
Base Oil Viscosity, ISO	320
Operating Temperature Range °C	-20° to +130°
Appearance	Smooth Tacky
Timkin OK Load, kg	18
Drop Point, °C	190
4-ball Weld Load, kg	400
Water Washout, 1hr/80°C, %	4