

**W 11-125 Quick (603623190) Angle Grinder**  
(220-240 V / 50 - 60 Hz); Cardboard box

Order no. 603623190  
EAN 4061792200593



Product may differ from Image



- Low fatigue as never before: compact angle grinder with smallest handle circumference in its class for perfect ergonomics
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

### Characteristics

|                              |                      |
|------------------------------|----------------------|
| Disc-Ø                       | 125 mm // 5 "        |
| Rated input power            | 1100 W               |
| Output power                 | 700 W                |
| No-load speed                | 11000 rpm            |
| Revolutions at rated load    | 7500 rpm             |
| Torque                       | 3.2 Nm / 28.3 in-lbs |
| Spindle thread               | M 14                 |
| Weight (without power cable) | 2.3 kg / 5.1 lbs     |
| Cable length                 | 4 m / 13 "           |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 5.8 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.6 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 93 dB(A)  |
| Sound power level (LwA)      | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Guard  
Side handle  
Inner support flange  
M-Quick flange nut