

## IS310



### Colours:

Silver	<input checked="" type="checkbox"/>
White	<input type="checkbox"/>
Black	<input type="checkbox"/>



### TOP QUALITY

Can be fitted to all types of doors, up to **160 kg** in weight and **1400 mm** in width.

Adjustment: closing speed, latching action or silent closing, backcheck, delayed closing action.

### IS310 STANDARD ARM

IS310 force EN 3-6 - finish: silver	<b>376100033</b>	1	-	1
IS310 force EN 3-6 - finish: white RAL9016	<b>376100034</b>	1	-	1
IS310 force EN 3-6 - finish: black RAL9005	<b>376100035</b>	1	-	1

### TECHNICAL SPECIFICATIONS

Force	3 - 6
Valve 1	Thermo-constant closing speed
Valve 2	Latching action
Valve 3	Backcheck (BC)
Valve 4	Delayed closing action between 140° and 75° (DC)
Force adjustment	Using BTR screw
Compliance EN1154	4   8   6 - 3   1   1   3
Compliance EN1634	Suitable for fire/smoke resistant doors
Opening angle	180°
Safety valve	Included
Type of arm	Standard arm
Condition for the use	Operational safety and comfort from -15°C to +40°C
Dimensions	302 x 74 x 51,5 (mm)
Product weight	2,75 kg