



2

ELECTRONIC & MECHANICAL
DIGITAL LOCKS RANGECARBINE
ELECTRONIC
DIGITAL LOCK

CDL2

- + Keyless entry using a pin code
- + Attractive slimline keypad with much smaller footprint than competitors
- + Simple keypad entry
- + Suits 35mm to 51mm door thickness
- + 60/70mm adjustable backset
- + Key override
- + Moisture and salt spray tested
- + Very easy to install, retrofits for standard locksets
- + Long lasting membrane keypad

The Carbine CDL2 digital locks range is the perfect addition to your home, investment property, short stay rental or small business. Available in both a lever set and deadbolt models, these digital locks compliment modern facades with a classy satin nickel or a slick matte black finish.

For a small footprint, the Carbine digital locks pack a punch, with up to 20 user codes with each code set up in 4 easy steps, auto lock mode as the door closes for added security, passage mode for super convenience especially throughout a busy day, vacation mode so you can set your digital lock to be opened by your master code, and a key override as a backup option.

The slimline designed Carbine Digital Lock is easy to install as it retrofits standard lockset sizes and is built to endure the daily grind with a long-lasting touch keypad, has been salt spray tested to 240 hours so you can feel confident it performs in coastal areas, cycle tested to 250,000 openings on the Lever set range and 100,000 cycles on the Deadbolt range with zero failures, and the convenience of using only 4 AAA (deadbolt use 4 AA) batteries which provides between 12 to 24 months of uninterrupted access.

Order today and upgrade to the Carbine standards of digital locks with the Carbine CDL2 digital lock range.

DEADBOLT MODEL:

- + 10 user codes
- + Uses 5 pin LKW5 (Silca LW4) keyway
- + Uses 4 x AA Procell batteries
- + Cycle tested to 100,000 cycles

LEVERSET MODEL:

- + 20 user codes
- + Uses 6 pin LKW9 (Silca LW5) keyway, supplied keyed to 5 pin
- + Uses 4 x AAA Procell batteries
- + Cycle tested to 250,000 cycles



Easily rekeyable



Volume control to turn on/off door lock operation volume



Fire Tested for 1 hour



Default auto-lock delay timer is 5 seconds (range 5-90 seconds)



Passage mode via internal turn button



Vacation mode



Low battery warning light and tone



**CEL-3IN1-NEX
CEL-3IN1-TRI**
Retrofit Plate
Available for
CDL2

CARBINE

THE NEXT GENERATION IN LOCKING

Access Lock Specialists Ltd

170 Waterloo Rd, Hornby, Christchurch, 8042, Christchurch, Ct
03 344 5959
admin@accesslocks.co.nz
<https://www.accesslocks.co.nz/>

