

ULTIMATE PRINT NYLON P4035

Ultimate Print Nylon 4035 is a Polyurethane transfer film (opaque white, 100 microns) with a special heat sealing adhesive for hydrophobic and impregnated nylon textiles.


Ultimate Print Nylon 4035 offers a high print resolution with a semi-matt finish. It is printable with Eco-Solvent and Solvent inks. Even filigree letters and motives can be cut and weeded after printing without any problem due to the non adhesive PET film liner.

Ultimate Print Nylon 4035 can be cut with all current plotters. We recommend using a standard 45° blade. After weeding, the cut flex film is transferred for 3 - 4 sec. by heat press. The PET liner should be removed lukewarm. After cooling down the material is to be pressed for another 10 - 15 sec. with the same parameters.

The soft, elastic transfer film offers a comfortable textile touch and high wearing comfort. Ultimate Print Nylon 4035 excels due to an excellent opacity. The raw materials are ecologically inert, do not contain PVC, plasticizers or heavy metals (in accordance with Oeko-Tex Standard 100 Class I).

Guarantee for secure and long-lasting bond of Ultimate Print Nylon is only given when following the specified temperature and pressure conditions. We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.



45° Blade Recommended



Print right reading.



150°C



2.0 bar Medium Pressure



Pre-press 4 seconds, remove PET-Liner press 10 seconds



Peel Warm



Wash cold (max 40°) inside out
Do Not Tumble Dry
Do Not Dry Clean



Do Not Layer.



Iron inside out. Do not iron directly onto transfers.



Suitable for Nylon.



Application tape required

Standard dimensions: 500 mm x 25m

TRANSFER FILM	ADHESIVE	THICKNESS	LINER
Polyurethane, cast	Polyamide-hotmelt	100 microns +/- 5 %	PET-film, non adhesive

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by the manufacturer.

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.