

PRODUCT SPECIFICATIONS

STYLETECH MISTY & RAINBOW SAM / SAR

Styletech Misty and Rainbow are a metalised range of materials with a stunning finish and amazing effect in different lighting.

Using the highest tack application tape is necessary for fast easier applications. Another trick for easy transfer of letters off the release paper is to squeegee both the back of the release paper as well as the application side before removing letters from the release paper.

Due to the various influences which occur from production and transfer of plotter lettering, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.



45° Blade Recommended



Cut this material right reading



Applies to most clean, dry, hard surfaces, such as metal, wood, glass, ceramic, acrylic, etc.



Application Tape recommended



Not recommended for washing. If washing is required, carefully hand wash.

Standard dimensions: 610mm x 45m

PHYSICAL PROPERTIES	ADHESION PROPERTIES oz./in.
PVC Film Thickness (mils) 2	PEEL PSTC - 1 (instant R.T.) 50 SHEAR PSTC 7 - 1000grams / 1 inch wide 250 hours no failure
RESISTANCE	SERVICE TEMPERATURE
Water: Excellent (submerged for 1 week in 20°C water, 24 hours after applied to substrate) Humidity: Excellent Abrasion: Good. Edge sealing recommended for certain holographic applications. Solvent: Good. Edge sealing for best results.	-40°C - 121°C
OUTDOOR DURABILITY	SHELF LIFE
Silver Chromes: Up to 2 years Diamond Deck Plate & Galvanised: Up to 2 years Gold Chromes recommended for indoor use only Holographics: Up to 2 years. Not recommended for Automotive use.	2 Years stored under 23°C and 50% relative humidity.

NOTE: All information based on tests believed to be reliable. These values do not constitute guaranty and do not constitute a warranty. Purchaser is to independently determine suitability of this material for specific purpose