

PRODUCT SPECIFICATIONS

STYLETECH OPAL SAO

Styletech Opal throws a stunning rainbow effect depending on the angle of light. These can be easily applied allowing you to turn any flat or glass surface into a work of art.

Using the highest tack application tape is necessary for fast easier applications. Another trick for easy transfer of letters off the release paper is to squeegee both the back of the release paper as well as the application side before removing letters from the release paper.

Due to the various influences which occur from production and transfer of plotter lettering, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.



45° Blade Recommended



Cut this material right reading



Applies to most clean, dry, hard surfaces, such as metal, wood, glass, ceramic, acrylic, etc.



Application Tape recommended



Not recommended for washing. If washing is required, carefully hand wash.

Standard dimensions: 610mm x 45m

PHYSICAL PROPERTIES	ADHESION PROPERTIES oz/in.
PVC Film Thickness (mil) 3.2 with permanent acrylic adhesive	PSTC 1 (Instant R.T) Stainless Steel 40
PSA Thickness (mils) 1	PSTC 1 (1 hour R.T) Stainless Steel 55
Elongation 50% - 100%	PSTC 1 (24 hour R.T) Stainless Steel 60
	PSTC 1 (72 hour R.T) Stainless Steel 65
RESISTANCE	APPLICATION TEMPERATURE
Resistance to mild alkalies and acids and to most petroleum based grease, oils and salt spray.	16°C-93°C
HEAT SHRINKAGE	SHELF LIFE
24 hours at 66°C 0.001mm	1 Year stored under 23°C and 50% relative humidity.
OUTDOOR DURABILITY	
When properly converted and applied (vertical exposure - non printed) up to 1 year.	

NOTE: All information based on tests believed to be reliable. These values do not constitute guaranty and do not constitute a warranty. Purchaser is to independently determine suitability of this material for specific purpose