

PRODUCT SPECIFICATIONS

HAIRLINE AH

Hairline is made on polyurethane, with a stunning 3D effect of hairline.

Hairline is suitable for transfer to textiles like cotton, polyester, cotton/polyester blends. This product requires a sharp blade as is thicker than most other HTV products.

We recommend using a standard 45° blade, however depending on your machine you may need a 60° blade.

Guarantee for a secure and long-lasting bond of Hairline is only given when following the specified temperature and pressure conditions. We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter lettering, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.



45° or 60° Blade Recommended



Cut this material in mirror image



140°C - 150°C



2,5 - 3,0 bar medium pressure



8 - 12 seconds



Warm/Hot Peel



Wash warm (max 40°C) inside out. Tumble Dry normal. Do NOT dry clean.



Layering not recommended



Iron inside out. Do not iron directly onto transfers.



Suitable for cotton, polyester, Cotton/Polyester blends



Application Tape not required.

THICKNESS

520 microns +/- 5 %

Standard dimensions: 450mm x 25m

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by the manufacturer.