

PRODUCT SPECIFICATIONS

METALLIC AM

Metallic Heat Transfer film leaves a gleaming metal finish and is perfect for any application.

Metallic heat transfer film is manufactured for transferring solid and metallic coloured logos, graphics or text onto fabrics for the production of eye catching and brilliant metallic designs.

Metallic is suitable for use on Cotton, Polyester, Cotton/Poly blends.

This product will not stretch.

Guarantee for secure and long-lasting bond of Metallic is only given when following the specified temperature and pressure conditions. We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter lettering, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.



45° Blade
Recommended



Cut this material in
mirror image



150°C - 160°C



2,0 - 3,0 bar
Medium pressure



10-12 Seconds



Peel Warm gently



Wash Cold (40°C) inside
out. Gentle Cycle. NOT
Suitable for Dry Cleaning.
Do NOT tumble dry.



Layering not
recommended



Iron inside out. Do
not iron directly onto
transfers.



Suitable for cotton,
polyester and cotton/
polyester blends



Application Tape not
required.

Standard dimensions: 500mm x 25m

THICKNESS

82 microns +/- 5 %

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by the manufacturer.

Important to note for AM444 Spectrum: There is a line that appears every 50-60cms during production that is unavoidable.