

PRODUCT SPECIFICATIONS

PEARLSHINE APS

Pearlshine Flex is the perfect combination of rich jewel-tone colors and a glistening finish. This specialty flex has the vibrant range of colors and design patterns available, makes eye-catching creations and accents.

It is stretchy and very easy to weed, soft and smooth.

Pearlshine is suitable for transfer to textiles like cotton, polyester, cotton/polyester blends.

We recommend using a standard 45° blade.

Guarantee for a secure and long-lasting bond of Pearlshine is only given when following the specified temperature and pressure conditions. We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter lettering, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.



45° Blade
Recommended



Cut this material in
mirror image



140°C - 150°C



2,5 - 3,0 bar
medium pressure



15 seconds



Warm/Hot Peel



Wash warm (max 40°C)
inside out.
Tumble Dry normal.
Do NOT dry clean.



Layering not
recommended



Iron inside out.
Do not iron directly
onto transfers.



Suitable for cotton,
polyester, Cotton/
Polyester blends



Application Tape not
required.

THICKNESS

100 microns +/- 5 %

Standard dimensions: 500mm x 25m

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by the manufacturer.