

STRETCH

POLI-FLEX® Stretch is a highly stretchable polyurethane film with a matt, reflection free surface, in accordance with Oeko-Tex Standard 100 Class I.

POLI-FLEX® Stretch is suitable to transfer onto textiles like cotton, mixtures of polyester/cotton and polyester/acrylic. It can be used for lettering on T-shirts, sport & leisure wear, sport bags and promotional articles.

We recommend using a standard 45° blade. After weeding, the cut film is transferred by heat press. The PET liner should be removed warm. The soft, high stretchable transfer film offers a comfortable textile touch and high wearing comfort.












POLI-FLEX® Stretch excels due to an excellent opacity and has a self-adhesive PET liner which enables repositioning.

The raw materials are ecologically inert, do not contain PVC, plasticizers or heavy metals (in accordance with Oeko-Tex Standard 100 Class I).

Guarantee for a secure and long-lasting bond of POLI-FLEX® STRETCH is only given when following the specified temperature and pressure conditions. We recommend evaluation on test material to determine suitability.

Polyester textiles (e.g. football shirts, soft shell jackets) are coloured with special dye. During the thermal transfer the colour particles are activated and could seep through the Stretch material. Therefore we recommend using Blockout Soft instead of Stretch.

Due to the various influences which occur from production and transfer of plotter lettering, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.

 45° Blade Recommended	 Cut this material in mirror image	 160°C	 2,5 - 3,0 bar Medium pressure
 15 Seconds	 Peel Warm	 Wash warm (max 80°C) inside out. Tumble Dry normal. Suitable for Dry Cleaning.	 Layering not recommended
 Iron inside out. Do not iron directly onto transfers.	 Suitable for cotton, mixtures of polyester/cotton and	 Application Tape not required.	

Standard dimensions: 500mm x 25m

TRANSFER FILM	ADHESIVE	THICKNESS	LINER
Polyurethane, cast	Polyurethane - hotmelt	100 microns +/- 5 %	PET-film, self adhesive

CODE	PRODUCT	SIZE	300mm	1m	2-9m	10m+	Full Roll/m	Full Roll
AS	Stretch	500mm	\$6.42	\$19.26	\$17.91	\$16.66	\$15.50	\$387.50

The colours displayed are representative of the vinyl colour only and may vary slightly to actual material.

All prices are subject to 10% GST.

Free delivery on all orders over \$150+gst.



AS401
White



AS402
Black



AS404
Green



AS406
Royal Blue



AS408
Red



AS410
Yellow