



**Chicago  
Pneumatic**



**Anytime.  
Anywhere.  
Any job.**

**XAS 27**

FEATURE	BENEFIT
<b>Honda Engine</b>	Very reliable with low emissions and superior global support.
<b>C55 Airend</b>	Efficient compressor that requires less power for higher performance.
<b>Rail belt system</b>	Accurate tensioning and stability for belt drive.
<b>Polyethylene components</b>	Superior resistance to dents, rust and extreme temperatures.
<b>Small dimensions</b>	Extremely flexible on where it can go - even through commercial doorways.
<b>Lightweight</b>	Very easy to tow & maneuver into the perfect working position.
<b>Integrated electric fan</b>	Efficient cooling.
<b>Recessed discharged valve</b>	Added protection where it counts.
<b>Torsion suspension</b>	Extra added stability for the road.
<b>Jockey wheel</b>	Easy to level ball coupling to vehicle.
<b>Sound attenuation</b>	Complies with strictest noise regulations.
<b>Trolley variant</b>	Very compact and affordable alternative.
<b>Support mounted</b>	Easy mounting.



PERFORMANCE		
Normal effective pressure	bar / psi	7 / 100
Free air delivery	l/s / cfm	27 / 57
Maximum effective pressure, unloaded	bar / psi	8 / 116
Maximum ambient temp at sea level	°C / °F	40 / 104
Minimum starting temp	°C / °F	-10 / 14
Sound power level / Sound pressure level	dB(A)	97 / 72

ENGINE	
Make	Honda
Type	GX630
Coolant	Air Cooled
Number of cylinders	2
Output @ 2900 RPM	14.1 kW / 18.9 HP
Fuel	Gasoline

CAPACITIES		
Compressor oil system	liter	4.0
Air receiver	liter	7.2
Fuel tank	liter	20
Capacity of engine oil sump	liter	1.7

Dimensions & Weight : Trolley		
Length	mm / inch	1290 / 50.8
Width	mm / inch	850 / 33.5
Height	mm / inch	958 / 37.7
Weight	kg	240

Dimensions & Weight : Std. Towable		
Length, towbar down	mm / inch	2159 / 85
Width	mm / inch	1003 / 39.4
Height	mm / inch	988 / 38.9
Weight	kg	270

Dimensions & Weight : Support Mounted		
Length	mm / inch	1280 / 50.4
Width	mm / inch	850 / 33.5
Height	mm / inch	787 / 31
Weight	kg	230