

Cup brush with thread, knotted wire

BT 600 Z



Product benefit

For aggressive brushing work on large, flat surfaces - For preparing metal surfaces before varnishing - Stable knotted wire design for easy cleaning and removal of slag, rust, scale and concrete residues

Application

Steel	●
Stainless steel	●

Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Stainless steel processing industry
- ▶ Railing construction
- ▶ Metal construction
- ▶ Steel construction
- ▶ Locksmith's shop

Diameter in mm	holding device	Fill material	Wire thickness in mm	Fill length in mm	Number of knots	Max. RPM	Packing unit/pcs.	Cat. number
65	thread M14	Steel	0,35	22	18	12500 rpm	1	358334
65	thread M14	Steel	0,50	22	18	12500 rpm	1	358335
65	thread M14	Stainless steel	0,50	22	18	12500 rpm	1	358340
80	thread M14	Steel	0,50	22	20	8500 rpm	1	358337
100	thread M14	Steel	0,50	27	22	8500 rpm	1	358338

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de

