

#### 2.2 - TYPICAL CHEMICAL 2.2 - TYPICAL MECHANICAL

# **PRODUCT INFORMATION**

Product / Tradename	Satincraft 13	Certificate No.	26303
Standard / Classification	AS/NZS 4855: B E4313A AWS/ASME-SFA A5.1: E6013	Date	19/10/22
	AWS/ASME-SFA AS.1. E0015	Batch No.	
			611182
		Consumable Type	Electrode
Size	2.5 mm	Country of Origin	Indonesia

### [2.2] - TYPICAL CHEMICAL ANALYSIS TYPICAL DATA: ACC TO EN 10204 2.2

C	Mn	Si	Р	S	Ni	Cr	Мо	V	Cu	Nb	Ti	AI	В	Zr
0.04	0.39	0.27	0.021	0.017	0.1	0.037	0.037	0.068						
Notes														

#### [2.2] - TYPICAL MECHANICAL PROPERTIES TYPICAL DATA: ACC TO EN 10204 2.2

#### TENSILE PROPERTIES

Condition As Welded		Shielding		
Test R <sub>p</sub> 0.2%   Temp 0.2% Yield		R <sub>m</sub> UTS	A₅ Elongation	
	Ambient	460 MPa	520 MPa	28%

### **IMPACT PROPERTIES**

#### TYPICAL DATA: ACC TO EN 10204 2.2

Temp	Impact Value	Lateral Expansion
0	60 J avg.	

# **OTHER MECHANICAL PROPERTIES - TYPICAL AVG.**

Hardness
----------

# **OTHER PROPERTIES / INFORMATION**

Diffusible Hydrogen (typical) ml H/100g weld metal	Radiographic Soundness
---	------------------------

### COMPLIANCE

Cigweld Pty. Ltd. certifies that the material listed in the certificate conforms to the listed specifications and this product is supplied under a QA Program fulfilling the EN ISO 9001 standard This certificate is produced electronically and is valid without signature.

Issued by Vida Mokhtar Quality Manager Reviewed by Damian Bibby Senior Brand Manager - Consumables

#### **Company Details**

Cigweld Pty Ltd 71 Gower Street, Preston Victoria, Australia, 3072 Tel: (03) 94747400 Fax: (03) 94747391