

VERISHIELD™ VS120F

PASSIVE FOLDING EARMUFF

PRODUCT CODE: 1035141-VS / 1035107-VS

HOWARD
LEIGHT



BY PIP



1035141-VS



1035107-VS

FEATURES

- » Fits a wide range of head sizes comfortably
- » Wide ear cup opening suits larger ears and hearing aids
- » Lightweight steel-wire headband with cushioned comfort fit
- » Precision micro-adjustments for secure fit and seal
- » Memory foam ear cushions for enhanced comfort and attenuation
- » ABS molded construction with internal baffle design for reduced weight
- » Oil-resistant cup surface ideal for heavy-duty environments
- » Air Flow Control technology delivers high attenuation without extra bulk
- » Optimised internal airflow design improves consistent noise reduction
- » Attenuation level marked on cup for quick on-site identification
- » Compact folding design for convenient storage, transport and protection between uses

SPECIFICATIONS

Attenuation Type: Passive

Noise Environment: Medium/High

Headband Material: PU Foam/Steel Wire

Cup Material: PVC/PU Foam/ABS

Operating Temperature Range: 0°C to +55°C

Weight: 227g

Colour: Black, Hi-Vis Yellow

Country of Origin: China

APPLICATIONS

Recommended for use in the following applications:

- » Construction
- » Manufacturing
- » Forestry
- » Mining
- » Oil and Gas
- » Utilities
- » DIY

PACKAGING

Unit: 1 | **Carton:** 10

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
FREQUENCY HZ	125	250	500	1000	2000	4000	8000
MEAN ATTENUATION	20.3	21.3	28.8	35.9	38.8	36.7	39.7
STANDARD DEVIATION	4.0	4.2	3.6	2.9	2.7	2.5	2.7
MEAN-MINUS-STANDARD DEVIATION ATTENUATIONS	16.3	17.1	25.2	33.0	36.1	34.2	37.0

SLC₈₀ Value is 31dB (Class 5)

STANDARDS

AS/NZS 1270:2002 Acoustic Hearing Protectors -
Class 5 SLC₈₀ 31dB



PIP ANZ (AUSTRALIA
& NEW ZEALAND)

AUSTRALIA
PHONE: 1300 747 269

NEW ZEALAND
PHONE: 0800 747 269

info@pipanz.com
www.pipanz.com

PIP
GLOBAL SAFETY