

AirSoft® EARPLUG

Product description

Advanced Air Pocket Design utilising advances in acoustical engineering, AirSoft's new internal fins create an interlocking, noise blocking barrier within the air pocket, providing dependable attenuation for all wearers upon proper insertion. AirSoft also attenuates better across the entire frequency range, offering the highest in multiple-use protection with an SLC80 26dB Class 5.

Optimised for exceptional in-ear comfort, AirSoft's new four flange profile creates a better seal in the ear canal, delivering optimal protection and increased comfort for long-term wear. At the same time, AirSoft's firm stem and tapered shape facilitates easy insertion and removal, and allows the earplug to sit comfortably in the ear canal.

FEATURES

- Optimised for Superior Fit, Comfort and Protection.
- Easier Handling – Firm stem facilitates proper insertion and removal.
- Improved Comfort – Soft rounded flanges, baffled air pocket feels more comfortable in your ear.
- SLC80 26dB – Highest attenuation in multiple use earplugs, ideal for medium and high levels of hazardous noise exposure.
- Blue Color – Contrasting color ideal for process industries that require visual inspection.
- Available corded or uncorded with flip top box, of safety impact case packaging options.

APPLICATIONS

- Any noise environment 105dB to less than 110dB



DPAS-30W



AS-1



AS-30R

DPAS-30R

Technical Details

Material:	Thermoplastic Elastomer
Diameter:	12.19mm
Length:	31.55mm
Cord Length:	711.2mm -
Cord Material:	PVC (red), Nylon (white)
Weight:	0.91g
Colour:	Blue
Storage Case:	Polybag or PVC or Impact case - polypropylene
Temperature:	-26°C to +60°C

Standards

- Approved to AS/NZS 1270:2002
- License number 1579
- SLC80 26dB Class 5

Frequency	125	250	500	1000	2000	4000	8000
Mean Value dB	33.0	32.6	32.3	31.9	33.9	35.6	40.6
Std Deviation dB	8.1	9.3	10.2	9.3	6.5	8.4	6.1
Mean-Std Dev dB	25.0	23.3	22.1	22.6	27.4	27.3	34.5

Ordering Details

PART NO.	DESCRIPTION	MIN QTY	BOX QTY	BOX DIMENSIONS	BOX WEIGHT	CASE DIMENSIONS	CASE WEIGHT	BARCODE
AS-1	Uncorded, reusable case	1	50	203 x 197 x 129	727g	650 x 205 x 426	7.27kg	033552000242
AS-30R	Polycord, reusable case	1	50	203 x 197 x 129	818g	650 x 205 x 426	8.18kg	033552000372
DPAS-30R	Red vinyl cord, polybag	1	100	203 x 197 x 129	725g	650 x 205 x 426	7.25kg	033552000969
DPAS-30W	White nylon cord, polybag	1	100	203 x 197 x 129	689g	650 x 205 x 426	6.89kg	033552001034

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM HONEYWELL SAFETY PRODUCTS AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL SAFETY PRODUCTS RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

Honeywell Safety Products Australia Pty Ltd

Australia 1300 139 166
New Zealand 0800 322 200
www.honeywellsafety.com

Doc | Rev | 09/16
© 2016 Honeywell Safety Products Australia Pty Ltd