

TITAN P.E.T STRAPPING BATTERY TOOLS



Innovative systems for plastic strapping. Fast operation to tension and seal your goods securely and easily...

Fast operation to tension and seal your goods securely and easily. Ideal for challenging loads that require a more secure and rigid strapping solution.



KEY FEATURES

- ▶ Can be used with PET or Poly Strapping
- ▶ Extremely fast operation – less than 5 seconds to tension and seal your goods securely
- ▶ New strap guide system allows use of different strap widths without adjusting tool
- ▶ User-friendly touch panel with simple to adjust controls
- ▶ Ergonomically designed and lightweight for minimum operator hand fatigue
- ▶ Supplied with charger (charge time 15-30 minutes) and 1 battery

ORDER INFO

CODE	DESCRIPTION
42.620	TITAN TA220
42.621	TITAN TA250
42.623	TITAN TA411
42.624	TITAN TA450

**Talk to us
today to
arrange a
demo!**

PS05_42.62



PRODUCT INFO

Titan Battery operated strapping tools are ideal for efficient joining of plastic strapping. These tools tension, weld and cut the strapping in one simple operation. Ideally suited for large users in manufacturing, warehousing, masonry and timber industries.

The Titan™ battery strapping tools are made in Italy and offer extremely reliable functionality and low maintenance. The tools create a friction weld seal which provides secure load retention and eliminates the need for using metal seals.

SPECIFICATIONS

TITAN



Product	TITAN TA 220 The light weight tool for lower tension applications	TITAN TA 250 The mid-sized all rounder	TITAN TA 411 The large sized tool for heavy duty applications	TITAN 450 The ultimate large sized tool with the latest functionality
Joint	Friction Weld Joint	Friction Weld Joint	Friction Weld Joint	Friction Weld Joint
Weight	Approx. 3.9kg	Approx. 3.9kg	Approx. 3.9kg	Approx. 4.1kg
Dimensions (LxWxH)	318 x 130 x 183mm	300 x 150 x 160mm	318 x 130 x 183mm	300 x 150 x 160mm
Strap Tensioning	2200N	2500N	5000N	5500N
Strap Feeding Speed	200mm/sec	266mm/sec	200mm/sec	200mm/sec
Battery	LiPo 14.8v	LiPo 14.8v	LiPo 14.8v	LiPo 14.8v
Strap Type	PP / PET	PP / PET	PP / PET	PET
Strap Widths	12mm to 16mm	12mm to 16mm	15mm to 19mm	15mm to 19mm
Strap Thickness	0.5-1.05mm	0.5-1.05mm	0.7-1.27mm	0.7-1.30mm