


## **DOE NETWORK WALL MOUNT SERVER RACKS**

# **NCWMXXXDOE**



### **DESCRIPTION**

CERTECH DoE racks are manufactured around universal 19" standards, providing the ability to use our racks with universal 19" equipment from vendors worldwide. All racks are constructed from high quality cold rolled steel & are shipped fully assembled for quick deployment

#### **STANDARDS**

 Complies with IEC-60297, ANSI/EIA RS-310-D, IEC297-2, DIN41491; PART1, DIN41494; PART7, GB/T3047.2-92, IP20 rated

#### **FEATURES**

- Wall or floor installation type
- 180 degree locks
- Convenient and quick wall mounting
- · No assembly required
- Compatible with 19" International Standard and Metrical and ETSI standards
- 2 year warranty on cabinets.
  Subject to use within the static loading specifications and operation within normal environmental conditions

#### PRODUCT SPECIFICATIONS

Product Type	DoE Wall Mount Rack	
Static Loading Capacity:	60kgs	
Colour:	Black (RAL 9004) powder coated paint	
Material:	SPCC quality cold rolled steel, gloss black colour, easy clean surface	
Mounting Profile Thickness:	2.0mm	
Mounting Angle Thickness:	1.5mm	
Surface Finish:	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting	
Mounting Hole Type:	Square	
Door Style:	Single honeycomb style	
Side Panels:	Single piece, lockable & removable	
Security:	Keyed alike doors & side panels	
Assembly:	Supplied complete	
Compliance:	IEC-60297, ANSI/EIA RS-310-D, IEC297-2, DIN41491-1, DIN41494-7, GB/T3047.2-92	



NCWM18600DOE	RU	WxDxH (External)	Shipping dimensions
	18RU	600mm x 600mm x 908mm	660mm x 660mm x 980mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		425mm	570mm

www.certech.com.au • 1300 144 111 • info@certech.com.au ABN: 17 149 306 785