

IP45 RATED DUAL DOOR OUTDOOR FREESTANDING CABINET



DESCRIPTION

CERTECH IP rated racks are designed to protect sensitive network equipment from harsh environments where equipment may be exposed to dust or water. If you need a tough & robust rack, then look no further than CERTECH IP45 & IP65 rated racks, available in wall mounted & free-standing options. All racks are manufactured to universal 19" standards, providing the ability of use with universal 19" equipment from vendors worldwide. All racks are constructed from SGCC with a zinc powder coating or SUS316 stainless steel, and they are shipped fully assembled for quick deployment. CERTECH racks are covered by a 2-year warranty, subject to use within the static loading specifications and operation within normal environmental conditions.

FEATURES

- IP Rating
- Fans
- Cable Entry
- Rack Mounting Compatibility
- Vertical Mounting Rails
- Ventilation & Dust Filters
- Front & Rear Doors

DETAILS

Rack Type	Free-Standing IP45 Rated
Static Loading Capacity	800kg
Colour	Grey
Material	SGCC+Zinc Powder Coated
Mounting Hole Type	Square
Security	Lockable front & rear doors
Assembly	Fully Welded Construction
Warranty (Rack)	2-year warranty. Subject to use within the static loading specifications and operation within normal environmental conditions
Warranty (Fans)	1-year warranty

IP45 RATED DUAL DOOR OUTDOOR FREESTANDING CABINET

NROD188X8GY-DD-V2		RU	WxDxH (External)	Shipping dimensions
	18RU		850mm x 849mm x 1,119mm	885mm (w) x 915mm (d) x 1,280mm (h)
			Set distance between front and rear mounting rails	Max useable space (front to rear door)
			603mm	761mm
		INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails		
NROD188X10GY-DD-V2		RU	WxDxH (External)	Shipping dimensions
	18RU		850mm x 1,067mm x 1,119mm	915mm (w) x 1,115mm (d) x 1,280mm (h)
			Set distance between front and rear mounting rails	Max useable space (front to rear door)
			805mm	968mm
		INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails		
NROD248X8GY-DD-V2		RU	WxDxH (External)	Shipping dimensions
	24RU		850mm x 849mm x 1395mm	885mm (w) x 915mm (d) x 1,520mm (h)
			Set distance between front and rear mounting rails	Max useable space (front to rear door)
			603mm	761mm
		INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails		
NROD278X8GY-DD-V2		RU	WxDxH (External)	Shipping dimensions
	27RU		850mm x 849mm x 1519mm	885mm (w) x 915mm (d) x 1,650mm (h)
			Set distance between front and rear mounting rails	Max useable space (front to rear door)
			603mm	761mm
		INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails		
NROD278X10GY-DD-V2		RU	WxDxH (External)	Shipping dimensions
	27RU		850mm x 1,067mm x 1,519mm	915mm (w) x 1,115mm (d) x 1,650mm (h)
			Set distance between front and rear mounting rails	Max useable space (front to rear door)
			805mm	968mm
		INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails		

IP45 RATED DUAL DOOR OUTDOOR FREESTANDING CABINET

