

PREMIER SERIES SERVER RACKS

19" Server Racks - 600mm Wide

NSRXXXX



DESCRIPTION


CERTECH Premier Series 600mm wide racks are the ideal rack for any type of installation. All racks are manufactured around universal 19" standards, providing the ability to use our racks with universal 19" equipment from vendors worldwide. All racks are constructed from high quality cold rolled steel & are shipped fully assembled for quick deployment. CERTECH racks are covered by a 2-year warranty, subject to use within the static loading specifications and operation within normal environmental conditions.


FEATURES


- Front Glass Door
- Perforated Rear Split Doors
- Fans (drop-down tray)
- Cable Entry
- Adjustable Vertical Mounting Rails
- Integrated Earthing


DETAILS


Rack Type	NSR Premier Series
Static Loading Capacity	800kgs
Colour	Black (RAL 9004) powder coated paint
Material	SPCC quality cold rolled steel, easy clean surface
Mounting Profile Thickness	2.0mm
Mounting Angle Thickness	1.5mm
Surface Finish	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting
Mounting Hole Type	Square
Door Style	Australian approved toughened glass front door. Rear perforated steel, honeycomb style
Side Panels	Single piece, removable
Security	Keyed alike doors & side panels
Assembly	Fully assembled
Warranty (Rack)	2-year warranty. Subject to use within the static loading specifications and operation within normal environmental conditions
Warranty (Fans)	1-year warranty
Compliance	IEC-60297, ANSI/EIA RS-310-D, IEC297-2, DIN41491-1, DIN41494-7, GB/T3047.2-92


NSR126X6		RU	WxDxH (External)	Shipping dimensions
			600mm x 600mm x 745mm	690mm x 700mm x 765mm
	12RU	Set distance between front and rear mounting rails		Max useable space (front to rear door)
		400mm		520mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet				


NSR126X7		RU	WxDxH (External)	Shipping dimensions
			600mm x 700mm x 745mm	690mm x 800mm x 765mm
	12RU	Set distance between front and rear mounting rails		Max useable space (front to rear door)
		500mm		620mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet				


NSR126X8		RU	WxDxH (External)	Shipping dimensions
			600mm x 800mm x 745mm	690mm x 900mm x 765mm
	12RU	Set distance between front and rear mounting rails		Max useable space (front to rear door)
		600mm		720mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet				


NSR186X6		RU	WxDxH (External)	Shipping dimensions
			600mm x 600mm x 1010mm	690mm x 700mm x 1030mm
	18RU	Set distance between front and rear mounting rails		Max useable space (front to rear door)
		400mm		520mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet				


NSR186X7		RU	WxDxH (External)	Shipping dimensions
			600mm x 700mm x 1010mm	690mm x 800mm x 1030mm
	18RU	Set distance between front and rear mounting rails		Max useable space (front to rear door)
		500mm		620mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet				


NSR186X8		RU	WxDxH (External)	Shipping dimensions
			600mm x 800mm x 1010mm	690mm x 900mm x 1030mm
	18RU	Set distance between front and rear mounting rails		Max useable space (front to rear door)
		600mm		720mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet				


NSR226X6	RU	WxDxH (External)	Shipping dimensions
	22RU	600mm x 600mm x 1190mm	690mm x 700mm x 1210mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		400mm	520mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			


NSR226X9	RU	WxDxH (External)	Shipping dimensions
	22RU	600mm x 900mm x 1190mm	690mm x 1000mm x 1210mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		700mm	820mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			


NSR276X6	RU	WxDxH (External)	Shipping dimensions
	27RU	600mm x 600mm x 1410mm	690mm x 700mm x 1430mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		400mm	520mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			


NSR276X8	RU	WxDxH (External)	Shipping dimensions
	27RU	600mm x 800mm x 1410mm	690mm x 900mm x 1430mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		600mm	720mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			


NSR276X9	RU	WxDxH (External)	Shipping dimensions
	27RU	600mm x 900mm x 1410mm	690mm x 1000mm x 1430mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		700mm	820mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			


NSR276X10	RU	WxDxH (External)	Shipping dimensions
	27RU	600mm x 1000mm x 1410mm	690mm x 1100mm x 1430mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		800mm	920mm
INCLUDES: 4 x fans, 1 x shelf, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			


NSR376X6	RU	WxDxH (External)	Shipping dimensions
	37RU	600mm x 600mm x 1855mm	690mm x 700mm x 1875mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		400mm	520mm
INCLUDES: 4 x fans, 2 x shelves, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			


NSR376X8	RU	WxDxH (External)	Shipping dimensions
	37RU	600mm x 800mm x 1855mm	690mm x 900mm x 1875mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		600mm	720mm
INCLUDES: 4 x fans, 2 x shelves, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			


NSR376X10	RU	WxDxH (External)	Shipping dimensions
	37RU	600mm x 1000mm x 1855mm	690mm x 1100mm x 1875mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		800mm	920mm
INCLUDES: 4 x fans, 2 x shelves, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			


NSR426X6	RU	WxDxH (External)	Shipping dimensions
	42RU	600mm x 600mm x 2080mm	690mm x 700mm x 2100mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		400mm	520mm
INCLUDES: 4 x fans, 3 x shelves, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			


NSR426X8	RU	WxDxH (External)	Shipping dimensions
	42RU	600mm x 800mm x 2080mm	690mm x 900mm x 2100mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		600mm	720mm
INCLUDES: 4 x fans, 3 x shelves, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			

NSR426X9	RU	WxDxH (External)	Shipping dimensions
	42RU	600mm x 900mm x 2080mm	690mm x 1000mm x 2100mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		700mm	820mm
INCLUDES: 4 x fans, 3 x shelves, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			

NSR426X10	RU	WxDxH (External)	Shipping dimensions
	42RU	600mm x 1000mm x 2080mm	690mm x 1100mm x 2100mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		800mm	920mm
INCLUDES: 4 x fans, 3 x shelves, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			

NSR456X6	RU	WxDxH (External)	Shipping dimensions
	45RU	600mm x 600mm x 2210mm	690mm x 700mm x 2230mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		400mm	520mm
INCLUDES: 4 x fans, 3 x shelves, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			

NSR456X8	RU	WxDxH (External)	Shipping dimensions
	45RU	600mm x 800mm x 2210mm	690mm x 900mm x 2230mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		600mm	720mm
INCLUDES: 4 x fans, 3 x shelves, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			

NSR456X10	RU	WxDxH (External)	Shipping dimensions
	45RU	600mm x 1000mm x 2210mm	690mm x 1100mm x 2230mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		800mm	920mm
INCLUDES: 4 x fans, 3 x shelves, 25 x cage nuts, 1 x horizontal 6 outlet PDU, 4 x castor wheels & levelling feet			