

## CERTECH 8 Port 16A Switched PDU



### FEATURES:

- Current Meter: Digital True RMS Current Meter
- Power Monitor: Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols: Http, Https, SNMP, DHCP, UDP
- Outlet Control: Individual Outlet Control
- Power Delay: Power On/Off Sequence can be Defined
- Alarm Thresholds: User-Defined Alarm Thresholds for Warning and Overload
- Event Alert: Email, Trap, Audible Alarm

### General:

- Output: (8) IEC 320 C13
- Input: (1) IEC320 C20 Inlet; IEC320 C19 to C20 Power Cord 3M
- Protection: (1) 16 AMP Circuit Breaker

### Communication:

- SSL Indication: (1) Yellow LED
- DHCP Indication: (1) Green LED
- Output Status: (8) Green LED
- Network: (1) RJ45 for Ethernet
- Current Meter: 3 Digits Seven Segments for True RMS Meter  
Range: 0A ~ 20 A  
Resolution: 0.1A  
Precision: +/-2%/+/-0.1AMP

### Operation:

- Nominal Voltage: 230V
- Voltage: 200V~ 240V full range
- Frequency: 50/60HZ full range
- Max. Output Current: 16 Amp
- Temperature: 0 ~ 40 Celsius degree
- Humidity: 0% ~ 90%
- Size: 90 x 432 x 44 mm
- Weight: 3 kg

### Regulatory Approvals:

CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006  
FCC Part 15 Class A, ICES-003

