

Shurfoam

Heavy duty chlorinated foaming cleaner

Description

Shurfoam is a heavy duty, chlorinated alkaline foam cleaner, designed for daily use in the food, beverage and dairy industries.

VF₆

Key properties

- •Shurfoam is a caustic-based, alkaline foam cleaner containing a high level of hypochlorite and a blend of chelating agent and surfactant/wetting agents. It is very effective for use on a wide range of food soils including animal and vegetable fats, blood and proteins. In addition, its high chlorine content rapidly removes organic and vegetable-based stains and helps to prevent build-up of protein film deposits.
- •Shurfoam is recommended for daily cleaning in vegetable processing, canning, wine and soft drink production. It is also suitable for applications where heavy proteinaceous soiling is encountered, such as abattoirs, poultry processors and the fish industry. It can be used for cleaning floors, walls, cutting tables, packing fillers, conveyors and other processing equipment.
- •Shurfoam is suitable for use with a wide range of foam application equipment.

Benefits

- Effective on all types of food soiling
- •Rapid stain removal
- •Helps prevent build-up of protein film
- •Free rinsing



For additional information, please contact us at: Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 www.diversey.com

Shurfoam

Heavy duty chlorinated foaming cleaner

Use Instructions

Use Shurfoam at the following concentrations depending on application and soil type.

Foam Cleaning: 1. Pre-rinse surface to remove gross soiling. 2. Using a foam applicator, apply Shurfoam at 10-50ml/L water (1%-5%v/v), depending on soil loading. 3. Allow foam to stand for approximately 5-10 minutes. 4. Rinse product contacting surfaces with potable water after use.

Manual Cleaning: 1. Prepare a 5-10ml/L water (0.5%-1%v/v) solution of Shurfoam. 2. Apply with brush, cloth or mop. 3. For heavy soils allow to penetrate for 5-10 minutes. 4. Rinse product contacting surfaces with potable water after use.

Soaking: 1. Pre-rinse equipment to remove gross soiling. 2. Prepare a 10-50ml/L water (1%-5%v/v) solution of Shurfoam. 3. Soak for 15-30 minutes. 4. Rinse product contacting surfaces with potable water after use.

Shurfoam can be used for cleaning areas within a large processing room provided the room can be divided into distinct areas. No edible product or packaging material may be present in the area during cleaning and there can be no possibility of contamination of product or packaging material as a result of cleaning.

Product compatibility

Shurfoam when applied at the recommended concentration and temperature is suitable for use on the grades of stainless steel commonly found in the processed food industry. It is unsuitable for use on soft metals such as aluminium and galvanised materials. Always rinse surfaces thoroughly after use (within 1 hour). In the event of uncertainty it is advisable to evaluate individual materials before any prolonged use.

Approvals

In New Zealand: NZFSA approved C38 (All animal product except dairy). Passed AsureQuality assessment for food/beverage/dairy/factories food contact surfaces h1460 with conditions.

Product Specifications

Appearance	Clear pale yellow liquid
Relative density @ 20℃	1.15
pH (1% solution at 20°C)	12.0

The above data is typical of normal production and should not be taken as a specification

Safe handling and storage information

Store in original closed containers or (where applicable) in an approved bulk tank, away from sunlight and extreme temperatures. Keep away from acids. Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet.

Safety Reminder:

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.diversey.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:

Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 www.diversey.com

