



SAFETY DATA SHEET

1. Identification

Product identifier Ultra Cutting Creme

Other means of identification

Product Code 1319

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Presta Products
Address 361 Fairview Ave
Barberton, OH 44203
United States

Telephone Phone 800-253-2526
Fax 330-777-8317

Website www.prestaproducts.com

E-mail msdsinfo@malcopro.com

Contact person Technical Department

Emergency phone number Phone 1-800-424-9300

Supplier Not available.

Distributor in New Zealand

Pacer Car Clean Products NZ LTD
33 Ha Crescent Wiri,
Auckland, New Zealand
Telephone: +64 9 25000 91
Fax: +64 9 25000 92
Web: www.pacer.co.nz

24hr Emergency Assistance in New Zealand

National Poison Control Center:
0800 Poison [764 766]

2. Hazard identification

Physical hazards Flammable liquids Category 4

Health hazards Acute toxicity, inhalation Category 5

Specific target organ toxicity, repeated exposure Category 2

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement Combustible liquid. May be harmful if swallowed. Causes serious eye irritation. May be harmful if inhaled. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe mist/vapors. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response IF INHALED: Call a POISON CENTER/doctor if you feel unwell. Get medical advice/attention if you feel unwell. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information 15.3992606948% of the mixture consists of component(s) of unknown acute oral toxicity. 57% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 57% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
KEROSENE		8008-20-6	5 - < 10

Chemical name	Common name and synonyms	CAS number	%
propane-1,2,3-triol		56-81-5	5 - < 10
Solvent Naphtha (Petroleum), Medium Aliph.		64742-88-7	5 - < 10
Other components below reportable levels			70 - < 80

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all R- and H-phrases is displayed in section 16.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician or poison control center immediately.
Skin contact	Take off immediately all contaminated clothing. Remove and isolate contaminated clothing and shoes. Immediately flush skin with plenty of water. Get medical attention immediately. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Consider initial downwind evacuation for at least 500 meters (1/3 mile). Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. All equipment used when handling the product must be grounded. Do not breathe mist/vapors. Do not get this material in contact with eyes. Do not get this material in contact with skin. Do not get this material on clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear positive pressure self-contained breathing apparatus (SCBA). Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Keep at temperature not exceeding 49 °C. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in a closed container away from incompatible materials. Keep container tightly closed. Store in a well-ventilated place. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	Non-aerosol.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components	Type	Value	Form
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	Vapor.
propane-1,2,3-triol (CAS 56-81-5)	TWA	10 mg/m3	Mist.

Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances Workers Compensation Board, as amended

Components	Type	Value	Form
propane-1,2,3-triol (CAS 56-81-5)	TWA	3 mg/m3	Respirable mist.
		10 mg/m3	Total mist

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended

Components	Type	Value	Form
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	Non-aerosol.

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	Type	Value	Form
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	Non-aerosol.

Canada. Ontario OELs (Regulation 833, Control of Exposure to Biological or Chemical Agents), as amended

Components	Type	Value	Form
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	Non-aerosol.

Canada. Quebec OELs (Regulation respecting occupational health and safety, v. S-2.1, r.13), as amended

Components	Type	Value	Form
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	
propane-1,2,3-triol (CAS 56-81-5)	TWA	10 mg/m3	Mist.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996; Table 21), as amended

Components	Type	Value	Form
KEROSENE (CAS 8008-20-6)	15 minute	250 mg/m3	Vapor.
propane-1,2,3-triol (CAS 56-81-5)	15 minute	20 mg/m3	Mist.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Canada - Alberta OELs: Skin designation

KEROSENE (CAS 8008-20-6) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

KEROSENE (CAS 8008-20-6) Danger of cutaneous absorption

Canada - Ontario OELs: Skin designation

KEROSENE (CAS 8008-20-6) Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

KEROSENE (CAS 8008-20-6) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Can be absorbed through the skin.

KEROSENE (CAS 8008-20-6) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

KEROSENE (CAS 8008-20-6) Danger of cutaneous absorption

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection Do not get in eyes. Face-shield. Chemical respirator with organic vapor cartridge and full facepiece. Eye wash fountain is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of an impervious apron is recommended. It may provide little or no thermal protection.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Physical state	Liquid.
Form	Liquid. Cream.
Color	Yellow

Odor	Vanilla
Melting point/freezing point	3632 °F (2000 °C) estimated
Boiling point or initial boiling point and boiling range	4420.3 °F (2437.95 °C) estimated
Flammability	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	0.7 % estimated
Explosive limit - upper (%)	Not available.
Flash point	176.8 °F (80.4 °C) estimated 176.7 °F (80.4 °C) estimated
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
pH	8.7
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water) (log value)	Not available.
Vapor pressure	0.12 hPa estimated
Density and/or relative density	
Density	10.64 lb/gal
Vapor density	Not available.
Particle characteristics	Not available.
Other information	
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Oxidizing properties	Not oxidizing.
VOC	16.95 % by weight estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Risk of ignition.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be harmful if inhaled.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Harmful in contact with eyes.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity May be harmful if inhaled.

Components	Species	Test Results
KEROSENE (CAS 8008-20-6)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5200 mg/m ³ , 4 Hours
propane-1,2,3-triol (CAS 56-81-5)		
Acute		
Inhalation		
LC50	Rat	> 570 mg/m ³ , 1 Hours
Oral		
LD50	Rat	5.57 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

propane-1,2,3-triol (CAS 56-81-5) Irritant

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

KEROSENE (CAS 8008-20-6) A3 Confirmed animal carcinogen with unknown relevance to humans.

Canada - Manitoba OELs: carcinogenicity

KEROSENE (CAS 8008-20-6) Confirmed animal carcinogen with unknown relevance to humans.

Canada - Quebec OELs: Carcinogen category

KEROSENE (CAS 8008-20-6) Detected carcinogenic effect in animals.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Hazardous by OSHA criteria. Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
propane-1,2,3-triol (CAS 56-81-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	51000 - 57000 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential	No data available.
Partition coefficient n-octanol / water (log Kow) propane-1,2,3-triol	-1.76
Mobility in soil	No data available.
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

15. Regulatory information

Canadian regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.
-----------------------------	---

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations	This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work. The product is classified and labelled in accordance with EC directives or respective national laws. Pregnant women should not work with the product, if there is the least risk of exposure.
----------------------------------	--

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

NEW ZEALAND:

HSR002525 Cleaning Products
(Combustible) Group Standard 2020

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 08-13-2024

Revision date 08-13-2024

Version # 03

Further information HMIS® is a registered trade and service mark of the NPCA.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Presta Products cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Revision information Product and Company Identification: Alternate Trade Names
Physical & Chemical Properties: Multiple Properties