RC SERIES

The Australian owned and designed* Trueheat RC Series of Gas Cooking Equipment has been developed for the restaurant and cafe market with a high quality finish, designed to fulfill the busy demands within a commercial kitchen.

16mm thick steel griddle plate with 16.5MJ/hr burner per 300mm section. 100% Flame failure controls included as standard. Piezo ignition on concealed burners.

DIMENSIONS & WEIGHT

External Dimension: 600W x 803D x 455H mm

Net Weight: 85kg

Working height: 910mm (with stand)

Combustible wall clearance: Side: 150mm, Rear: 150mm

TECHNICAL DATA

Gas Type: Natural or Propane

Total Output(MJ/hr): Natural Gas Propane Gas

Burner Ratings (MJ/hr): Natural Gas Propane Gas Ignition Type

Griddle per 300mm: 16.5 16.5 Piezo

Gas Connection: 3/4" Female

AGA approval number: AGA 6652 G

SHIPPING DATA

Shipping Weight: 104.5kg

Shipping Dimensions: 680W x 900D x 590H mm

OPTIONAL ACCESSORIES

Part Number:	Description:
RCSTD6	600mm Stand complete with shelf
B05002	Adjustable leg for RCT countertop mounting
MS-CSTRB	Castor with brake to suit both 600mm and 900mm
MS-CSTR	Castor without brake to suit both 600mm and 900mm
432018-900HK	900mm ¾ flexible gas hose with quick connect fittings and restraint
432018-1200HK	1200mm ¾ flexible gas hose with quick connect fittings and restraint

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Note: Stands fitted with castors will need to be cut down by 120-150mm.


*manufactured in China


RCT6-6G


600mm WIDE GRIDDLE MODULAR TOP



Stand sold separately









National Head Office 156 Swann Drive

Derrimut VIC 3026 +61 3 8369 4600 Tel: Fax: +61 3 8369 4699 96-100 Tope Street South Melbourne VIC 3205 +61 3 8699 1200 Tel: Fax: +61 3 8699 1299

Melbourne

Sydney

20/4 Avenue of the Americas Newington, NSW 2127

Tel: +61 2 8775 9500 Fax: +61 2 9648 4762

Brisbane

1/62 Borthwick Avenue Murarrie QLD 4172 Tel: +61 7 3900 2700 Fax: +61 7 3399 5311

Perth

Unit 16, 7 Abrams Street Balcatta, WA 6021 Tel: +61 8 6217 0700 Fax: +61 8 6217 0799