



**Model:**

□ CIMO825



CIMO825 ON B42

**Features and Benefits**

- 22.25" (565 mm) wide space-saving design.
- Produces up to 418 kg of ice per day.
- *Energy and Environment*
  - Exceeds new 2018 DOE (Department of Energy) regulations.
  - Up to 20% more energy efficient than other models.
  - Environmentally friendly, including BPA-free plastic and recyclable parts.
- *Sanitation*
  - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
  - Built in Agion® ensures unbeatable antimicrobial protection.
  - Smart LED light indicates machine status and when cleaning is required.
  - Simple, one-touch controls for sanitization and descaling.
  - BPA-free snap-in, snap-out dishwasher-safe components.
- *Unique Dual Exhaust* - Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- *Universal Smart Harness™* control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

CIMO825 CUBE ICE MAKER

**Ice Form**

FULL CUBE DIMENSIONS	
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (mm)	10 x 22 x 22



**CUBE**

**Bin Chart** Kits for Combining Wider Bins with Smaller Models

ICE STORAGE BINS										
	Model No.	B25	ICB110SC	B40	B42	ICB180SC	B55	ICB230SC	CIB400	B110
	Capacity	110 kg	110 kg	156 kg	160 kg	180 kg	232 kg	232 kg	400 kg	388 kg
	Width	762 mm	560 mm	762 mm	559 mm	760 mm	762 mm	764 mm	1,220 mm	1,219 mm
Kits	CIMO825	BT55	Kit Not Required	BT55	Kit Not Required	BT55		BT100		

\*See Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

**Options & Accessories**

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIMO825	CD200B	CD200B


Note: All modular cube CIM units can be installed with manufacturer approved ozone delivery systems.

**Ice Maker Warranty**

COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labour
Evaporator and Compressor	5 YEARS parts



CIMO825 CUBE ICE MAKER



### Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".

### Operating Requirements

	MINIMUM	MAXIMUM
		50Hz
Ambient Temp. Range Air	10 °C	43 °C
Water Temp.	4.4 °C	
Water Pressure	1.4 BAR	5.5 BAR

### Dimensions

ALL MODELS	
W x D x H (mm)	565 x 616 x 683

### Specifications

Model Number	Cond. Unit	Half-Cube Ice Production per 24hrs		Water Usage litres per 45 kg of Ice @ 32°C air/21°C water		kWH Used per 45 kg of ice @ 32°C air/21°C water	Watts Used Per Hr @ 32°C air/21°C water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Refrigeration Capacity per hour
		21°C air/10°C water (kg)	32°C air/21°C water (kg)	Potable	Condenser						
CIMO825A	Air	418	329	68	-	473	1440	220-240/50/1	10.8	16	4,206

\* Daily ice production based on half cube configuration. When installing a CIM on a drink dispenser, the KCUBEDISPB MUST be used.

Notes:  
 Number of Wires: 3 (including ground)  
 Approx. Shipping Weight lbs (kg): CIMO825A 100  
 Refrigerant Type: R404A