Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	XL Stainless Steel Cleaner Aerosol 500ml
Product Code:	STAINAERO500
Uses:	Stainless Steel Cleaner, Polish and Protector.
Company:	Integra Industries Limited
Address:	21A Grosvenor St
	Kensington, Dunedin
Telephone:	+64 3 455 6805
Email:	sales@integraindustries.co.nz
Emergency Number 24 hr:	0800 764 766 (0800 POISON) National Poison Centre

Section 2 – HAZARDS IDENTIFICATION

Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ.

Classified as a dangerous goods for transport purposes.

GHS Classifications:	HSNO Classifications:	
Aerosol Category 1	2.1.2A	Flammable aerosol
Aquatic toxicity Category 4	9.1D	May cause long lasting harmful effects to aquatic life.



Signal Words: Danger

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated
H413	May cause long lasting harmful effects to aquatic life.

Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Mineral Oil	8042-47-5	30 - 60
Ethanolamine	141-43-5	0 - 1
Hydrocarbon propellant (LPG - Propane, Butane)	68476-85-7	30 - 60
Non-hazardous ingredients		to 100

Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE (0800 764 766) or doctor.

Eye contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
Skin contact:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.
Inhalation:	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
Ingestion:	IF SWALLOWED: Call a POISON CENTRE or doctor. Do NOT induce vomiting. Obtain immediate medical attention.
Notes to physician:	Treat symptomatically and supportively. No specific antidote.
Section 5 – FIRE-FIGHTIN	G MEASURES
General fire hazards	Pressurised, extremely flammable aerosol.
Specific hazards:	Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. May float and be re- ignited on surface water. Will burn if involved in a fire.
Further advice:	On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion.
Extinguishing media:	For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam.
	For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment.
	Do NOT use straight streams of water.
Protective equipment	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Firefighting instructions	In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers from fire area if you can do so without risk. Runoff can cause environmental damage.
Hazchem Code:	2YE
Section 6 – ACCIDENTAL	RELEASE MEASURES
Minor spills:	Clean up all spills immediately. Provide ventilation. Remove all sources of ignition. If safe to do so, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Wash with water.
Major spills:	Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal. Wash area down with excess water.
Section 7 – HANDLING A	ND STORAGE
Handling Precautions:	Read product label before use. Keep out of reach of children. This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even after use.
Storage:	Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling. Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.
Section 8 – EXPOSURE C	ONTROLS/PERSONAL PROTECTION
Exposure Limits:	No value assigned for product. Exposure standards for constituents (NZ WES);

	Material	TWA, mg/m ³	STEL, mg/m ³
	Mineral Oil Mist	5	-
	Ethanolamine	7.5	15
	LPG (Liquefied petroleum gas – butane, propane)	1,800	-
Additional Information:	Wash hands before eating, drinking and smoking.		
Engineering Controls:	No controls required when handling small quantities. Use outdoors or with adequate ventilation.		
	Larger quantities: General exhaust is adequate under no equipment and lighting should be explosion-resistant.	ormal operating condition	s. Ventilation
Protective Equipment:	Generally not required for small quantities. In an industrial environment: gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.		
	In case of inadequate ventilation wear respiratory prote respirator with a type A filter.	ction. If TWA is exceeded	, wear an approved

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

pH: A	About 9.0
pii. A	
Vapour Density: >	> 1 (Air =1)
Vapour Pressure, kPa: 30	300 - 600
Boiling Point, °C: A	About 100
Melting Point, °C: N	Not applicable.
Specific Gravity: A	About 0.92
Flash Point, °C: <	< 0 (propellant)
Explosion Limit, % v/v:	EL 1.2% UEL 9.5%
Autoignition Temp, °C: N	Not applicable.
Solubility: Pa	Partially soluble in water.

Section 10 – STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.	
Section 11 – TOXICOLOGICAL INFORMATION		
Basis for Assessment:	Information given is based on product testing, and/or similar products, and/or components.	
Acute Oral Toxicity:	LD_{50} calculated to be > 5,000 mg/kg (based on component mixture).	
Acute Dermal Toxicity:	LD_{50} calculated to be > 5,000 mg/kg (based on component mixture).	
Acute Inhalation Toxicity:	LC_{50} calculated to be > 16 mg/L, Rat 4 hour (based on component mixture). Slightly toxic.	
	Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.	
Skin Irritation:	Prolonged or repeated contact may cause defatting of the skin and dermatitis.	
Eye Irritation:	Direct contact with spray may be irritating to the eye.	
Respiratory Irritation:	Inhalation of vapours or mists may cause irritation to the respiratory system.	
Sensitisation:	Product is not expected to be a sensitiser.	
Mutagenicity:	Not expected to be mutagenic.	

Carcinogenicity:	Product is not a suspected human carcinogen.
Reproductive toxicity:	Product is not a suspected human reproductive or developmental toxicant.
Specific Target Organ Toxicity	r: Product is not expected to be harmful to human target organs or systems.
Repeated Dose Toxicity:	Prolonged and repeated contact with product may result in contact dermatitis in sensitive persons.
Additional Information:	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

Section 12 – ECOTOXICITY INFORMATION

Ecotoxicity:	Ecotoxic in the aquatic environment with long lasting effects.
Mobility:	Product is partially volatile and large proportion will rapidly evaporate to the air if released into water.
Persistence/degradability:	More volatile components are expected to degrade in air. Some components may be persistent.

Section 13 – DISPOSAL CONSIDERATIONS

Material Disposal:	Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
	Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.
Container Disposal:	Recycle empty container if possible. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.

Section 14 – TRANSPORT INFORMATION

Transport:	Classified as a Dangerous Good for transport purposes.
	Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7. They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.
Proper Shipping Name:	Aerosols
UN Number:	1950
Dangerous Goods Class:	2.1
Transport Labels Required:	Class 2 Flammable (Land, Sea and Air)
	Land, Sea, Air
Subsidiary Risk:	Not applicable
Packing Group:	Not applicable
Marine Pollutant:	No
EMS Number	F-D, S-U (UN 1950 Flammable aerosols)
DG Segregation:	This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous

Section 15 – REGULATORY INFORMATION

```
Inventory Listing
```

NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.

Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

SDS regulations	This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017 (Consolidated Sept 2022).	
EPA Approval Number:	HSR002515 Aerosols (Flammable) Group Standard 2020	
EPA Hsno Controls:	Refer to www.epa.govt.nz for information on Controls.	
	This substance is to be managed using the conditions specified in an applicable Group Standard.	

Section 16 – OTHER INFORMATION

Additional information	Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.		
Abbreviations	CAS	Chemical Abstract Service number	
	EMS	Emergency Response Procedures for Ships Carrying Dangerous Goods	
	EPA	Environmental Protection Agency	
	GHS	Globally Harmonized System	
	IARC	International Agency for Research on Cancer	
	ΙΑΤΑ	International Air Transport Association	
	IMDG	International Maritime Dangerous Goods	
	LC ₅₀	Lethal Concentration, 50% / Median Lethal Concentration	
	LD ₅₀	Lethal Dose, 50% / Median Lethal Dose	
	LEL	Lower Explosion Limit	
	mg/m³	Milligrams per Cubic Metre	
	NZIoC	New Zealand Inventory of Chemicals	
	N.O.S.	Not otherwise specified	
	OEL	Occupational Exposure Limit	
	PEL	Permissible Exposure Limit	
	STEL	Short-Term Exposure Limit	
	STOT-RE	Specific target organ toxicity (repeated exposure)	
	STOT-SE	Specific target organ toxicity (single exposure)	
	TLV	Threshold Limit Value	
	TWA	Time Weighted Average	
	UEL	Upper Explosion Limit	

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product.

End of sds.