


TERGOSTRIP DP

DI Phase Immersion Paint Stripper



Description

Tergostrip DP is a liquid, heavy duty paint stripper designed for use in a dip bath operation. A water seal is used to minimise evaporation loss, drag out and to help in the removal of loosened paint. Tergostrip DP is carefully formulated to give efficient stripping of modern organic coatings including some baked powder coatings.

Chemical & Physical Properties

- | | |
|------------------------|------------------|
| • Appearance: | Thin Hazy Liquid |
| • Specific Gravity: | 1.2 Approx. |
| • Flammability : | Non Flammable |
| • Solubility in Water: | Emulsifiable |
| • pH: | 2.0 Approx. |

Application & Method Of Use

Application:

- Tergostrip DP will effectively remove epoxy and other tenacious coatings.
- Tergostrip DP may be used in a mild steel tank of reasonable thickness.

Method of Use:

- Fill tank to be used with Tergostrip DP taking care not to splash on skin or eyes. Protective clothing should be worn at all times when working with Tergostrip DP. Add a water seal of (10-13) centimeters but not more than 20% of the bath volume's height.
- Immerse work to be stripped in the bottom layer. **Avoid immersing any parts of the work in the top layer.**
- Inspect periodically for degree of stripping. Do not immerse for longer than four (4) hours.
- When stripping is complete, withdraw the work slowly, allow to drain and then hose off with a strong jet of water.
- Follow up by paint pre-treatment and/or painting system.

Dilution Ratio

- See Application & Method of Use above.

Precautions

Refer to Hazard Identification as per Safety Data Sheet.

TERGOSTRIP DP

DI Phase Immersion Paint Stripper

Safety, Transport & Storage Information

Please refer to Safety Data Sheet.

Packaging

Available in 20L & 200L containers. Containers non-returnable.

IMPORTANT: FOR DETAILED INFORMATION ABOUT THIS PRODUCT PLEASE REFER TO SAFETY DATA SHEET.

The product information contained in this document is to the best of our knowledge and non-binding. Our statements relating to possible uses of the product do not constitute a guarantee that such uses are appropriate in a particular user's case or that such uses do not infringe the patents or proprietary rights of any third party. We assume no risk or liability whatever in connection with any particular use, if not expressly confirmed by us in writing. Therefore Chemetall grants no warranty and does not accept any liability in connection with this product information or its use. Except where noted otherwise, all registered trademarks are owned by Chemetall or its affiliated companies. The reproduction of any or all of the information contained in this document is expressly forbidden without Chemetall's prior written consent.