DENTAURUM Australia Pty

Print date: 26.03.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cold model hardener

Revision date: 16.01.2024 Product code: 167-215 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Cold model hardener

Further trade names

Article No.: 167-215-00

UFI: WKWC-VJ39-9WMC-KQ46

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Health services.

1.3. Details of the supplier of the safety data sheet

Supplier: DENTAURUM GmbH & Co. KG Company name:

ABN: 79 055 919 787 Street: Turnstr. 31

Street address: 18 Bertram St, Mortlake NSW 2137 D-75228 Ispringen Place:

Telephone: +61 2 9743 4811 Telephone: +49 7231 803 0 Fax No: +61 2 9743 4599 e-mail: info@dentaurum.de Contact: Materials Manager

Contact person: Chemie

Internet: www.dentaurum.com

1.4. Emergency telephone +497231803-184 7:00-16:15 (Mo-Do) 7:00-13:15 (Fr) +497231803-0 16:15-18:00 (Mo-Do) 13:15-18:00 (Fr) number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 STOT SE 3: H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

n-butyl acetate

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smokina.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. Call a POISON CENTER/doctor if you feel unwell. P312

P403+P235 Store in a well-ventilated place. Keep cool.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cold model hardener

Revision date: 16.01.2024 Product code: 167-215 Page 2 of 9

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No 1272/2008)				
123-86-4	n-butyl acetate				
	204-658-1	607-025-00-1			
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066				
64-17-5	ethanol; ethyl alcohol				
	200-578-6	603-002-00-5			
	Flam. Liq. 2; H225				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol; ethyl alcohol	
	inhalation: LC50 = 95,6 mg/l (vapours); oral: LD50 = 6200 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink 1 glass of of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. Flammable.

5.3. Advice for firefighters



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cold model hardener

Revision date: 16.01.2024 Product code: 167-215 Page 3 of 9

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Avoid breathing vapours.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid breathing vapours.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. 30°C

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Health services.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cold model hardener

Revision date: 16.01.2024 Product code: 167-215 Page 4 of 9

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
123-86-4	n-Butylacetate	50	241		TWA (8 h)	EU
		150	723		STEL (15 min)	EU

8.2. Exposure controls





Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid breathing vapours.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Recommendation:

Dermatril Single-use gloves. NBR (Nitrile rubber). 0,11 mm

penetration time (maximum wearing period): 0 min.

REF 162-907-00 (7/S), REF 162-908-00 (8/M), REF 162-909-00 (9/L)

Camapren 720, 0,65 mm

penetration time (maximum wearing period): 10 min, KCL

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at:

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: brown, transparent

Odour: fruity

Melting point/freezing point:

-77 °C

Boiling point or initial boiling point and

126 °C

boiling range:

Flammability: not determined Lower explosion limits: 1,2 vol. %



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cold model hardener

Revision date: 16.01.2024 Product code: 167-215 Page 5 of 9

Upper explosion limits:7,5 vol. %Flash point:19 °CAuto-ignition temperature:370 °CDecomposition temperature:not determinedpH-Value (at 23 °C):6,5 (10%)

Water solubility: The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: 13 hPa

(at 20 °C)

Density (at 20 °C): 0,95 g/cm³
Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate: not determined Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable. Flammable,

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with: Alkali metals. Alkali (lye). Oxidizing agent.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64-17-5	ethanol; ethyl alcohol						
	oral	LD50 mg/kg	6200	Rat	IUCLID		
	inhalation (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS		



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cold model hardener

Revision date: 16.01.2024 Product code: 167-215 Page 6 of 9

Irritation and corrosivity

Irritant effect on the eye: irritant.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (n-Butyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

none

Additional information on tests

none

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

	or dadet le fret. Edetexile.						
CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
123-86-4	n-butyl acetate						
	Acute fish toxicity	LC50	62 mg/l	I	Leuciscus idus (golden orfe)		
64-17-5	ethanol; ethyl alcohol						
	Acute crustacea toxicity	EC50 14221 mg/l	9268 -	48 h	Daphnia magna	IUCLID	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol; ethyl alcohol	-0,31

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cold model hardener

Revision date: 16.01.2024 Product code: 167-215 Page 7 of 9

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Send to a hazardous waste incinerator facility under observation of official regulations.

List of Wastes Code - used product

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08);

waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent

mixtures; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:UN 186614.2. UN proper shipping name:Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Marine transport (IMDG)

14.1. UN number or ID number:UN 186614.2. UN proper shipping name:Resin solution

14.3. Transport hazard class(es):
14.4. Packing group:

Hazard label:
3



Special Provisions: Limited quantity: 5 L
Excepted quantity: E2
EmS: F-E, S-E



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cold model hardener

Revision date: 16.01.2024 Product code: 167-215 Page 8 of 9

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:UN 186614.2. UN proper shipping name:Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): 4 % (38 g/l) 2004/42/EC (VOC): 4 % (38 g/l)

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,12,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cold model hardener

Revision date: 16.01.2024 Product code: 167-215 Page 9 of 9

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

EmS: Emergency Schedules MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)