

# Safety Data Sheet

in accordance with HSNO

Date of issue: 04.08.2026

Revised On: 04.08.2026

## 1 Identification of the substance or mixture and of the supplier

### Other means of identification

**Trade name:** TRUCK BED COATING AUTO

**Article number:** 0000200041

**Product category:** PC9a Paints and coatings.

**Process category:** PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions  
PROC11 Non industrial spraying

**Application of the substance / the mixture:** Painting and coating.

**Uses advised against:** Any that differs from the recommended use.

**Manufacturer/Supplier:** Seymour of Sycamore  
917 Crosby Avenue  
Sycamore, IL 60178  
phone: 815-895-9101 www.seymourpaint.com

**Emergency telephone number:** 815-895-9101 if located outside the United States  
National Poisons Centre 0800 764 766

## 2 Hazards identification

### Classification of the substance or mixture

|                                                               |           |                                                                                                                         |
|---------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------|
| Aerosols Category 1                                           | H222-H229 | Extremely flammable aerosol. Pressurized container: may burst if heated.                                                |
| Eye irritation Category 2                                     | H319      | Causes serious eye irritation.                                                                                          |
| Carcinogenicity Category 1                                    | H350      | May cause cancer.                                                                                                       |
| Reproductive toxicity Category 2                              | H361      | Suspected of damaging fertility or the unborn child.                                                                    |
| Specific target organ toxicity - single exposure Category 3   | H336      | May cause drowsiness or dizziness.                                                                                      |
| Specific target organ toxicity - repeated exposure Category 2 | H373      | May cause damage to the central nervous system, the lung and the nervous system through prolonged or repeated exposure. |
| Hazardous to the aquatic environment chronic Category 3       | H412      | Harmful to aquatic life with long lasting effects.                                                                      |

### Additional information:

### Hazard pictograms



GHS02 GHS07 GHS08

### Signal word

Danger

### Hazard-determining components of labelling:

hexane  
Acetone

### Hazard statements

Paraffinnic Petroleum oil

Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes serious eye irritation.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to the central nervous system, the lung and the nervous system through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

### Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read carefully and follow all instructions.

Obtain special instructions before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear eye protection / face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/Information on ingredients

**Chemical characterisation: Mixtures** Classification according to HSNO Act 1996---2.1.2A Flammable Aerosols

**Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)

# Safety Data Sheet

in accordance with HSNO

Date of issue: 04.08.2026

Revised On: 04.08.2026

**Trade name: TRUCK BED COATING AUTO**

(Contd. of page 1)

**Dangerous components:**

|                                      |                                                                                                                                                                                                                                                                                                                                                                   |         |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| CAS: 74-98-6<br>EINECS: 200-827-9    | propane<br>Flammable gases Category 1A, H220                                                                                                                                                                                                                                                                                                                      | 15-25%  |
| CAS: 67-64-1<br>EINECS: 200-662-2    | Acetone<br>Flammable liquids Category 2, H225; Eye irritation Category 2, H319; Specific target organ toxicity - single exposure Category 3, H336<br>Specific concentration limit: Specific target organ toxicity - single exposure Category 3; H336: C ≥ 10 %                                                                                                    | 10-15%  |
| CAS: 8052-41-3<br>EINECS: 232-489-3  | Stoddard Solvent<br>Flammable liquids Category 3, H226                                                                                                                                                                                                                                                                                                            | 10-15%  |
| CAS: 106-97-8                        | n-butane<br>Flammable gases Category 1A, H220                                                                                                                                                                                                                                                                                                                     | 5-10%   |
| CAS: 110-19-0<br>EINECS: 203-745-1   | Isobutyl Acetate<br>Flammable liquids Category 2, H225                                                                                                                                                                                                                                                                                                            | 5-10%   |
| CAS: 110-54-3<br>EINECS: 203-777-6   | hexane<br>Flammable liquids Category 2, H225; Reproductive toxicity Category 2, H361; Specific target organ toxicity - repeated exposure Category 1, H372; Aspiration hazard Category 1, H304; Hazardous to the aquatic environment chronic Category 2, H411; Skin irritation Category 2, H315; Specific target organ toxicity - single exposure Category 3, H336 | ≥5-<10% |
| CAS: 108-65-6<br>EINECS: 203-603-9   | PM acetate<br>Flammable liquids Category 3, H226                                                                                                                                                                                                                                                                                                                  | 1-5%    |
| CAS: 1330-20-7<br>EINECS: 215-535-7  | xylene (mix)<br>Flammable liquids Category 3, H226; Acute dermal toxicity Category 4, H312; Acute inhalation toxicity Category 4, H332; Skin irritation Category 2, H315                                                                                                                                                                                          | 1-5%    |
| CAS: 14807-96-6<br>EINECS: 238-877-9 | Talc<br>Specific target organ toxicity - single exposure Category 3, H335                                                                                                                                                                                                                                                                                         | 1-5%    |
| CAS: 1333-86-4<br>EINECS: 215-609-9  | Carbon black                                                                                                                                                                                                                                                                                                                                                      | 1-5%    |
| CAS: 64741-88-4<br>EINECS: 265-090-8 | Paraffinic Petroleum oil<br>Carcinogenicity Category 1, H350                                                                                                                                                                                                                                                                                                      | 0.2-1%  |

**4 First aid measures**

|                                                                                   |                                                                                  |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| <b>After inhalation:</b>                                                          | Supply fresh air; consult doctor in case of complaints.                          |
| <b>After skin contact:</b>                                                        | Generally the product does not irritate the skin.                                |
| <b>After eye contact:</b>                                                         | Rinse opened eye for several minutes under running water. Then consult a doctor. |
| <b>After swallowing:</b>                                                          | Do not induce vomiting; call for medical help immediately.                       |
| <b>Information for doctor:</b>                                                    |                                                                                  |
| <b>Most important symptoms and effects, both acute and delayed</b>                | Dizziness                                                                        |
| <b>Indication of any immediate medical attention and special treatment needed</b> | No further relevant information available.                                       |

**5 Fire fighting measures**

|                                                              |                                                                  |
|--------------------------------------------------------------|------------------------------------------------------------------|
| <b>Extinguishing agents:</b>                                 | CO2, powder or water spray. Fight larger fires with water spray. |
| <b>Special hazards arising from the substance or mixture</b> | Can form explosive gas-air mixtures.                             |
| <b>Protective equipment:</b>                                 | Mount respiratory protective device.                             |
| <b>Additional information</b>                                | Cool endangered receptacles with water spray.                    |

**6 Accidental release measures**

|                                                                            |                                                                              |
|----------------------------------------------------------------------------|------------------------------------------------------------------------------|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Use respiratory protective device against the effects of fumes/dust/aerosol. |
| <b>Environmental precautions:</b>                                          | Do not allow product to reach sewage system or any water course.             |
| <b>Methods and material for containment and cleaning up:</b>               | Dispose contaminated material as waste according to section 13.              |

**7 Handling and storage**

|                                                                     |                                                                                                                                                                                                                              |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Precautions for safe handling</b>                                | Use only in well ventilated areas.                                                                                                                                                                                           |
| <b>Fire/explosion protection:</b>                                   | Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.<br>Do not spray onto a naked flame or any incandescent material. |
| <b>Conditions for safe storage, including any incompatibilities</b> |                                                                                                                                                                                                                              |
| <b>Requirements to be met by storerooms and receptacles:</b>        | Suitable material for receptacles and pipes: steel or stainless steel.                                                                                                                                                       |
| <b>Information about storage in one common storage facility:</b>    | Not available.                                                                                                                                                                                                               |

(Contd. on page 3)

# Safety Data Sheet

in accordance with HSNO

Date of issue: 04.08.2026

Revised On: 04.08.2026

Trade name: TRUCK BED COATING AUTO

**Specific end use(s)** No further relevant information available.

(Contd. of page 2)

## 8 Exposure controls/personal protection

### Ingredients with limit values that require monitoring at the workplace:

#### 74-98-6 propane

WES Simple asphyxiant; may present an explosion hazard

#### 67-64-1 Acetone

WES Short-term value: 2375 mg/m<sup>3</sup>, 1000 ppm  
Long-term value: 1185 mg/m<sup>3</sup>, 500 ppm  
bio

#### 8052-41-3 Stoddard Solvent

WES Long-term value: 525 mg/m<sup>3</sup>, 100 ppm

#### 106-97-8 n-butane

WES Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

#### 110-19-0 Isobutyl Acetate

WES Short-term value: 713 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

#### 110-54-3 hexane

WES Long-term value: 72 mg/m<sup>3</sup>, 20 ppm  
bio, oto

#### 1330-20-7 xylene (mix)

WES Long-term value: 217 mg/m<sup>3</sup>, 50 ppm  
oto, bio

#### 1333-86-4 Carbon black

WES Long-term value: 3 mg/m<sup>3</sup>  
Suspected carcinogen

### Exposure controls

#### General protective and hygienic measures:

Wash hands before breaks and at the end of work.  
Do not eat or drink while working.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Protection of hands:

Protective gloves

Neoprene gloves

#### Eye protection:

The glove material has to be impermeable and resistant to the product.  
Tightly sealed goggles

## 9 Physical and chemical properties

**Appearance:** Aerosol.  
**Odour:** Aromatic  
**Odour threshold:** Not determined.  
**pH-value:** Not determined.  
**Melting point/freezing point:** Undetermined.  
**Initial boiling point and boiling range:** -44 °C (-47.2 °F)  
**Flash point:** -19 °C (-2.2 °F)  
**Flammability:** Extremely flammable.  
**Auto-ignition temperature:** 240 °C (464 °F)  
**Decomposition temperature:** Not determined.  
**Ignition temperature:** Product is not selfigniting.  
**Explosive properties:** In use, may form flammable/explosive vapour-air mixture.  
**Lower:** 1 Vol %  
**Upper:** 10.9 Vol %  
**Vapour pressure:** Not determined.  
**Density at 20 °C (68 °F):** 0.8 g/cm<sup>3</sup> (6.7 lbs/gal)  
**Relative density:** Not determined.  
**Vapour density:** Not determined.  
**Evaporation rate:** Not applicable.  
**Solubility:** Fully miscible.  
**Partition coefficient: n-octanol/water:** Not determined.  
**Viscosity:** Not determined.  
**Dynamic:** Not determined.  
**Kinematic:** Not determined.  
**Water:** 0.0 %

### Other information

Particle characteristics Not applicable.

Physical state Aerosol

(Contd. on page 4)

# Safety Data Sheet

in accordance with HSNO

Date of issue: 04.08.2026

Revised On: 04.08.2026

Trade name: TRUCK BED COATING AUTO

(Contd. of page 3)

## 10 Stability and reactivity

**Thermal decomposition / conditions to be avoided:** Stable at environment temperature.  
**Possibility of hazardous reactions** No dangerous reactions known.  
**Conditions to avoid** No further relevant information available.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

**Acute toxicity---** Based on available data, the classification criteria are not met.

### LD/LC50 values relevant for classification:

#### 110-19-0 Isobutyl Acetate

|      |      |                      |
|------|------|----------------------|
| Oral | LD50 | 4,763 mg/kg (rabbit) |
|------|------|----------------------|

#### 108-65-6 PM acetate

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 8,500 mg/kg (rat) |
| Inhalative | LC50/4 h | 35.7 mg/l (rat)   |

#### 1330-20-7 xylene (mix)

|            |          |                      |
|------------|----------|----------------------|
| Oral       | LD50     | 8,700 mg/kg (rat)    |
| Dermal     | LD50     | 2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 6,350 mg/l (rat)     |

#### 1333-86-4 Carbon black

|      |      |                    |
|------|------|--------------------|
| Oral | LD50 | 10,000 mg/kg (rat) |
|------|------|--------------------|

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.  
**Serious eye damage/irritation** Causes serious eye irritation.  
**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.  
**Germ cell mutagenicity** Based on available data, the classification criteria are not met.  
**Carcinogenicity** May cause cancer.  
**Reproductive toxicity** Suspected of damaging fertility or the unborn child.  
**STOT-single exposure** May cause drowsiness or dizziness.  
**STOT-repeated exposure** May cause damage to the central nervous system, the lung and the nervous system through prolonged or repeated exposure.  
**Aspiration hazard** Based on available data, the classification criteria are not met.

## 12 Ecological information

**Aquatic toxicity:** No further relevant information available.  
**Persistence and degradability** The product is biodegradable after prolonged adaptation.  
**Bioaccumulative potential** No further relevant information available.  
**Mobility in soil** No further relevant information available.  
**Remark:** Harmful to fish  
**General notes:** Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Harmful to aquatic organisms

## 13 Disposal considerations

**Uncleaned packaging:**  
**Recommendation:** Disposal must be made according to official regulations.  
**Recommended cleansing agents:** Water, if necessary together with cleansing agents.

## 14 Transport information

|                                             |                                                                                                          |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------|
| UN-Number                                   | UN1950                                                                                                   |
| NZS, IMDG, IATA                             | UN1950                                                                                                   |
| UN proper shipping name                     |                                                                                                          |
| NZS                                         | 1950 AEROSOLS                                                                                            |
| Transport hazard class(es)                  |                                                                                                          |
| Class                                       | 2 5F Gases.                                                                                              |
| Label                                       | 2.1                                                                                                      |
| IMDG, IATA                                  |                                                                                                          |
| Class                                       | 2.1 Gases.                                                                                               |
| Label                                       | 2.1                                                                                                      |
| Packing group                               |                                                                                                          |
| NZS, IMDG, IATA                             | Void                                                                                                     |
| Environmental hazards:                      | Not applicable.                                                                                          |
| Special precautions for user                | Warning: Gases.                                                                                          |
| Hazard identification number (Kemler code): | -                                                                                                        |
| EMS Number:                                 | F-D,S-U                                                                                                  |
| Stowage Code                                | SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. |

(Contd. on page 5)

# Safety Data Sheet

in accordance with HSNO

Date of issue: 04.08.2026

Revised On: 04.08.2026

Trade name: TRUCK BED COATING AUTO

**Segregation Code**

(Contd. of page 4)

For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
For AEROSOLS with a capacity above 1 litre:  
Segregation as for the appropriate subdivision of class 2.  
For WASTE AEROSOLS:  
Segregation as for the appropriate subdivision of class 2.

**Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

**Transport/Additional information:****NZS**

Limited quantities (LQ)  
Excepted quantities (EQ)

1L  
Code: E0  
Not permitted as Excepted Quantity

**Transport category**

2

**Tunnel restriction code**

D

**IMDG**

Limited quantities (LQ)  
Excepted quantities (EQ)

1L  
Code: E0  
Not permitted as Excepted Quantity  
UN 1950 AEROSOLS, 2.1

**UN "Model Regulation":****15 Regulatory information****New Zealand Inventory of Chemicals**

|             |                                           |
|-------------|-------------------------------------------|
| 74-98-6     | propane                                   |
| 67-64-1     | Acetone                                   |
| 8052-41-3   | Stoddard Solvent                          |
| 110-19-0    | Isobutyl Acetate                          |
| 110-54-3    | hexane                                    |
| 108-65-6    | PM acetate                                |
| 28262-63-7  | Acrylic Resin                             |
| 1330-20-7   | xylene (mix)                              |
| 14807-96-6  | Talc                                      |
| 1333-86-4   | Carbon black                              |
| 64742-47-8  | Mineral Spirits                           |
| 64742-48-9  | Naphtha, hydrotreated heavy               |
| 100-41-4    | ethyl benzene                             |
| 112926-00-8 | Silicon Dioxide                           |
| 22464-99-9  | solid zirco drier                         |
| 64-17-5     | ethyl alcohol                             |
| 55349-01-4  | Polyamide Wax                             |
| 64741-88-4  | Paraffinnic Petroleum oil                 |
| 64742-89-8  | VM&P Naphtha                              |
| 136-52-7    | cobalt bis(2-ethylhexanoate)              |
| 136-51-6    | calcium bis(2-ethylhexanoate)             |
| 68611-44-9  | AEROSIL R972                              |
| 68953-58-2  | Alkyl Quaternary Ammonium Montmorillonite |
| 67-63-0     | Isopropyl Alcohol                         |
| 8002-43-5   | Soya Lecithin                             |
| 64742-95-6  | Solvent naphtha, light aromatic           |
| 7732-18-5   | Water                                     |

**HSNO Approval numbers**

|           |                  |           |
|-----------|------------------|-----------|
| 74-98-6   | propane          | HSR001010 |
| 67-64-1   | Acetone          | HSR001070 |
| 110-19-0  | Isobutyl Acetate | HSR001092 |
| 110-54-3  | hexane           | HSR001166 |
| 1330-20-7 | xylene (mix)     | HSR000983 |
| 1333-86-4 | Carbon black     | HSR002801 |

**Hazard-determining components of labelling:**

hexane  
Acetone  
Paraffinnic Petroleum oil

(Contd. on page 6)

# Safety Data Sheet

in accordance with HSNO

Date of issue: 04.08.2026

Revised On: 04.08.2026

Trade name: TRUCK BED COATING AUTO

(Contd. of page 5)

**Directive 2012/18/EU****Named dangerous substances - ANNEX I****Seveso category****Qualifying quantity (tonnes) for the application of lower-tier requirements****Qualifying quantity (tonnes) for the application of upper-tier requirements****Waterhazard class:**

None of the ingredients is listed.

P3a FLAMMABLE AEROSOLS

150 t

500 t

Water hazard class 2 (Self-assessment): hazardous for water.

**16 Other information****Relevant phrases**

H220 Extremely flammable gas.  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H350 May cause cancer.  
 H361 Suspected of damaging fertility or the unborn child.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.

**Department issuing SDS:**

Technical Services