

Safety Data Sheet

in accordance with HSNO

Printing date 19.07.2023

Revised On: 19.07.2023

1 Identification of the substance or mixture and of the supplier

Trade name: CHEVY ORANGE

Article number: EN00480000

Product category PC9a Paints and coatings.

Process category PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

Application of the substance / the mixture Painting and coating.

Uses advised against Any that differs from the recommended use.

Manufacturer/Supplier: Import Distribution T/A Formula
660B Cryers Road
East Tamaki
Auckland 2013
New Zealand

Emergency telephone number: National Poisons Centre 0800 764 766

2 Hazards identification

Classification of the substance or mixture

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H336 May cause drowsiness or dizziness.

Additional information:

Hazard pictograms



GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

Hazard statements

methyl isobutyl ketone

Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read carefully and follow all instructions.

Obtain special instructions before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear eye protection / face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/Information on ingredients

Chemical characterisation: Mixtures

Classification according to HSNO Act 1996---2.1.2A Flammable Aerosols

Description:

Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 Specific concentration limit: STOT SE 3; H336: C ≥ 10 %	25-50%
CAS: 74-98-6 EINECS: 200-827-9	propane Flam. Gas 1A, H220	15-25%
CAS: 106-97-8	n-butane Flam. Gas 1A, H220	5-10%
CAS: 110-19-0 EINECS: 203-745-1	Isobutyl Acetate Flam. Liq. 2, H225	5-10%
CAS: 108-65-6 EINECS: 203-603-9	PM acetate Flam. Liq. 3, H226	1-5%

(Contd. on page 2)

Safety Data Sheet

in accordance with HSNO

Printing date 19.07.2023

Revised On: 19.07.2023

Trade name: CHEVY ORANGE

(Contd. of page 1)

CAS: 108-10-1 EINECS: 203-550-1	methyI isobutyl ketone Flam. Liq. 2, H225; Carc. 2, H351; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336	1-5%
CAS: 107-87-9 EINECS: 203-528-1	MethyI Propyl Ketone Flam. Liq. 2, H225	1-5%
CAS: 2807-30-9 EINECS: 220-548-6	Glycol Ether EP Flam. Liq. 3, H226; Acute Tox. 4, H312; Eye Irrit. 2, H319	1-5%

4 First aid measures

After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Generally the product does not irritate the skin.
After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing:	Do not induce vomiting; call for medical help immediately.
Information for doctor:	
Most important symptoms and effects, both acute and delayed	Dizziness
Indication of any immediate medical attention and special treatment needed	No further relevant information available.

5 Fire fighting measures

Extinguishing agents:	CO2, powder or water spray. Fight larger fires with water spray.
Special hazards arising from the substance or mixture	Can form explosive gas-air mixtures.
Protective equipment:	Mount respiratory protective device.
Additional information	Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures	Use respiratory protective device against the effects of fumes/dust/aerosol.
Environmental precautions:	Do not allow product to reach sewage system or any water course.
Methods and material for containment and cleaning up:	Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling	Use only in well ventilated areas.
Fire/explosion protection:	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. Do not spray onto a naked flame or any incandescent material.
Conditions for safe storage, including any incompatibilities	
Requirements to be met by storerooms and receptacles:	Suitable material for receptacles and pipes: steel or stainless steel.
Information about storage in one common storage facility:	Not available.
Specific end use(s)	No further relevant information available.

8 Exposure controls/personal protection

Ingredients with limit values that require monitoring at the workplace:

67-64-1 Acetone

WES	Short-term value: 2375 mg/m ³ , 1000 ppm
	Long-term value: 1185 mg/m ³ , 500 ppm
	bio

74-98-6 propane

WES	Simple asphyxiant; may present an explosion hazard
-----	--

106-97-8 n-butane

WES	Long-term value: 1900 mg/m ³ , 800 ppm
-----	---

110-19-0 Isobutyl Acetate

WES	Long-term value: 713 mg/m ³ , 150 ppm
-----	--

108-10-1 methyI isobutyl ketone

WES	Short-term value: 307 mg/m ³ , 75 ppm
	Long-term value: 205 mg/m ³ , 50 ppm

(Contd. on page 3)

Safety Data Sheet

in accordance with HSN0

Printing date 19.07.2023

Revised On: 19.07.2023

Trade name: CHEVY ORANGE

(Contd. of page 2)

107-87-9 Methyl Propyl Ketone

WES Short-term value: 881 mg/m³, 250 ppm
Long-term value: 705 mg/m³, 200 ppm

Exposure controls**General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Neoprene gloves

Eye protection:

The glove material has to be impermeable and resistant to the product.
Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Form: Not determined.
Odour: Aromatic
Odour threshold: Not determined.
pH-value: Not determined.
Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: -44.5 °C (-48.1 °F)
Flash point: -19 °C (-2.2 °F)
Flammability (solid, gas):
Ignition temperature: 405 °C (761 °F)
Decomposition temperature: Not determined.
Auto-ignition temperature: Product is not selfigniting.
Explosive properties: In use, may form flammable/explosive vapour-air mixture.
Lower: 1.7 Vol %
Upper: 10.9 Vol %
Vapour pressure: Not determined.
Density at 20 °C (68 °F): 0.8 g/cm³ (6.7 lbs/gal)
Relative density: Not determined.
Vapour density: Not determined.
Evaporation rate: Not applicable.
Solubility: Fully miscible.
Partition coefficient: n-octanol/water: Not determined.
Viscosity: Not determined.
Dynamic: Not determined.
Kinematic: Not determined.
Water: 0.0 %
Other information: No further relevant information available.

10 Stability and reactivity

Thermal decomposition / conditions to be avoided: Stable at environment temperature.
Possibility of hazardous reactions: No dangerous reactions known.
Conditions to avoid: No further relevant information available.
Incompatible materials: No further relevant information available.
Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Acute toxicity--- Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**110-19-0 Isobutyl Acetate**

Oral	LD50	4,763 mg/kg (rbt)
------	------	-------------------

108-65-6 PM acetate

Oral	LD50	8,500 mg/kg (rat)
------	------	-------------------

Inhalative	LC50/4 h	35.7 mg/l (rat)
------------	----------	-----------------

108-10-1 methyl isobutyl ketone

Oral	LD50	2,100 mg/kg (rat)
------	------	-------------------

Dermal	LD50	16,000 mg/kg (rab)
--------	------	--------------------

Inhalative	LC50/4 h	11 mg/l (ATE)
------------	----------	---------------

		8.3-16.6 mg/l (rat)
--	--	---------------------

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

(Contd. on page 4)

Safety Data Sheet

in accordance with HSNO

Printing date 19.07.2023

Revised On: 19.07.2023

Trade name: CHEVY ORANGE

(Contd. of page 3)

Serious eye damage/irritation
Respiratory or skin sensitisation
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
STOT-single exposure
STOT-repeated exposure
Aspiration hazard

Causes serious eye irritation.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Suspected of causing cancer.
 Based on available data, the classification criteria are not met.
 May cause drowsiness or dizziness.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

12 Ecological information

Aquatic toxicity:
Persistence and degradability
Bioaccumulative potential
Mobility in soil
General notes:

No further relevant information available.
 The product is biodegradable after prolonged adaptation.
 No further relevant information available.
 No further relevant information available.
 Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

Uncleaned packaging:
Recommendation:
Recommended cleansing agents:

Disposal must be made according to official regulations.
 Water, if necessary together with cleansing agents.

14 Transport information

UN-Number	UN1950
NZS, IMDG, IATA	UN1950
UN proper shipping name	
NZS	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
Transport hazard class(es)	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1 Gases.
Label	2.1
Packing group	
NZS, IMDG, IATA	Void
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Segregation Code	
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
NZS	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

(Contd. on page 5)

Safety Data Sheet

in accordance with HSNO

Printing date 19.07.2023

Revised On: 19.07.2023

Trade name: CHEVY ORANGE

UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

(Contd. of page 4)

15 Regulatory information

New Zealand Inventory of Chemicals

67-64-1	Acetone
74-98-6	propane
110-19-0	Isobutyl Acetate
108-65-6	PM acetate
28262-63-7	Acrylic Resin
108-10-1	methyl isobutyl ketone
107-87-9	Methyl Propyl Ketone
2807-30-9	Glycol Ether EP
15793-73-4	Orange Pigment 34
5567-15-7	Diarylide Yellow Pigment 83
64742-47-8	Mineral Spirits
1330-20-7	xylene (mix)
22464-99-9	solid zirco drier
64742-88-7	Solvent naphtha (petroleum), medium aliph.
2786-76-7	Red Pigment 170
136-52-7	cobalt bis(2-ethylhexanoate)
100-41-4	ethyl benzene
1309-37-1	red iron oxide pigment
64742-89-8	VM&P Naphtha
136-51-6	calcium bis(2-ethylhexanoate)
68953-58-2	Alkyl Quaternary Ammonium Montmorillonite
67-63-0	Isopropyl Alcohol
8002-43-5	Soya Lecithin
7732-18-5	Water

HSNO Approval numbers

Approval Code: HSR002515

67-64-1	Acetone	HSR001070
74-98-6	propane	HSR001010
110-19-0	Isobutyl Acetate	HSR001092
108-10-1	methyl isobutyl ketone	HSR001194
107-87-9	Methyl Propyl Ketone	HSR001046
2807-30-9	Glycol Ether EP	HSR001161

Hazard-determining components of labelling:

methyl isobutyl ketone

Directive 2012/18/EU Named dangerous substances - ANNEX I

Seveso category

None of the ingredients is listed.
P3a FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements

150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements

500 t

Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Other regulations, limitations and prohibitive regulations

Group Standard: Aerosols (flammable) Group Standard 2006

16 Other information

Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

Department issuing SDS:

Technical Services