

# AO<sub>200T</sub>

Automatic Dispenser  
Piston Pump  
Simultaneous Dispensing



- ▶ Turbo Boost Speed: 350ml/min
- ▶ Minimum shot: 1/384Y(0.077ml)

**SANTINT • CHINA**

Add: Feilong Road, Xingyang,  
Zhengzhou, China  
Email: info@santint.com

**SANTINT • HOLLAND**

Add: Lageweg 35 - J, 2222 AG  
Katwijk The Netherlands  
Email: sales@santint-europe.com

**SANTINT • POLAND**

Add: ul. Postepu 19. mag.5  
02-676 Warszawa Polska  
Email: gianni.capozzi@santint.com

**SANTINT • U.S.A**

Add: 2000 Bloomingdale Road,  
Suite 220, Glendale Heights,  
IL 60139, U.S.A  
Email: frank@santint.com

**SANTINT • AUSTRALIA**

Add: 3 Technology Circuit  
Hallam Victoria, Australia  
Email: Info.AU@santint.com

# AO<sup>200T</sup> Automatic Dispenser FEATURES >>>

**SANTINT**  
WHERE INNOVATION MEETS PRECISION



1

## Piston Pump Simultaneous

Simultaneous dispensing of 5 canisters. Calibration-free and easy maintenance.



2

## Adjustable tube pressure sensor


When nozzle blockage is detected, machine stops dispensing and gives warning message to prevent tube explosion.



3

## Recirculation

No sedimentation, drying or block in tubes, minimizing malfunction.



4

## Turbo Boost Technology

Boost machine speed to 190% of its normal operating speed for a period of time that is enough to finish most of the jobs at Turbo Boost Speed.

\*For jobs with single colorant dispensing volume less than 49ml or 98ml when double filled.

- Dispensing Type: 5 Channel Simultaneous Dispensing
- Minimum Shot: 1/384Y(0.077ml)

- Canisters: Up to 32
- Canister Volume: 2.5L/4.5L
- Canister Material: POM

- Turbo Boost Speed: 350 ml/min

- Efficiency (Single Pump): 200ml/min

- Dimension: 880X775X1185 (16 cans) (WDXH)
- 1260X775X1185 (24 cans) (mm)
- 1690X865X1305 (32 cans)

- Power: 250W
- Power Supply: 240V/50Hz

**AO<sup>200T</sup>**  
Technical  
Parameters