



TECHNICAL DATA SHEET

ROCKEZE

A high-performance, light hydrocarbon-based rust preventative treated with the most advanced rust and corrosion inhibitors, dewatering agents and friction modifiers.

This product has limitless applications, from freeing rusty bolts to protecting the finest machined parts.

FEATURES

- The product is penetrative, i.e. it can reach the most remote and inaccessible areas
- Excellent dewatering properties
- Extremely high searching power ensures the release of all rust-bound parts
- Excellent performance even in the most demanding conditions
- Has a clean appearance, i.e. no thick greasy coating
- Protects all major metals and alloys
- Easy to apply due to its low viscosity
- It has an indefinite shelf life
- VOC-free, non-flammable formulation
- The product is easily removed with white spirits, kerosene and alkali degreasers

TYPICAL PHYSICAL CHARACTERISTICS

Density @ 15°C	0.824
Viscosity @ 40°C	3.3 cSt
Flash point	>70°C
Appearance	Clear amber liquid
Film Thickness	4 Microns
Days to Humidity Fail	60+ days
Water displacement	Pass
Product Code	04070

This data sheet and the information it contains is believed to be accurate as of the date of creation. Please email technical@rockoil.co.uk or telephone +44 (0) 1925 636191 if you require any further information.