



TECHNICAL DATA SHEET

GROUNDSMAN 2 STROKE

A high performance, semi-synthetic low ash 2 stroke engine oil.

Suitable for ECHO®, Husqvarna®, Makita®, McCulloch®, Oregon®, Partner® and Stihl® equipment (where specifications are appropriate), as well as most other land based horticultural or industrial equipment utilising a two stroke engine.

FEATURES

- Excellent wear protection provides a longer engine life
- Good thermal stability and deposit control leads to cleaner engines resulting in extended spark plug life, reduced ring sticking and prevention of detonation problems
- Designed for oil injection systems or premix applications
- Low smoke formulation results in a cleaner environment and improved operator comfort
- Suitable for use in petrol fuels incorporating up to 30% ethanol by volume.

PERFORMANCE SPECIFICATIONS, APPROVALS & RECOMMENDATIONS:

API	TC
JASO	FA, FB, FC, FD
ISO	L-EGB, L-EGC, L-EGD

TYPICAL PHYSICAL CHARACTERISTICS

Characteristic	Method	UoM	Typical
Density @ 15°C	ASTM D4052	g/cm ³	0.8700
Kinematic Viscosity @ 40°C	ASTM D445	mm ² /s	55.0
Flash Point (COC)	ASTM D92	°C	98
Pour Point	ASTM D97	°C	-18
Appearance	ASTM D4176-1	-	Clear & Bright
Colour	Visual	-	Red
Product Code	-	-	07122

This data sheet and the information it contains is believed to be accurate as of the date of creation. Please email technical@rockoil.co.uk or telephone +44 (0) 1925 636191 if you require any further information.