



# TECHNICAL DATA SHEET

## SYNTHESIS 2 INJECTOR

A synthetic two-stroke lubricant made from various synthetic base stocks, including Polyol Esters and Poly Iso Butylenes, which have been successfully coupled with advanced additive technology.

Synthesis 2 Injector is one of a range of synthetic lubricants and is an improved version of the hugely popular 'Synthesis 2'. This product is most suited for use in an injector system but has successfully been used as a premix oil.

### FEATURES

- Smokeless
- Easy Mixing
- Ultra Clean Burning
- High Lubricity - preventing oil-induced piston seizures
- High Shear Stability - Low Wear Rates
- Excellent fluidity

CAUTION: Synthesis 2 Injector must not be used with castor-based oils. Synthesis 2 Injector will mix with Leaded or Unleaded Petrol, Avgas and Octane Boosters but not Methanol.

### PERFORMANCE SPECIFICATIONS, APPROVALS & RECOMMENDATIONS:

JASO FD & FC

ISO-L-EGD

API TC

ROTAX 253

HUSQVARNA 346 & 372

Synthesis 2 Injector meets the requirements of SEA-DOO jet skis.

### TYPICAL PHYSICAL CHARACTERISTICS

Density @ 15°C	0.878
Viscosity @ 40°C	67.1 cSt
Pour Point	<-30 °C
Appearance	Clear yellow liquid
Product Code	07130

This data sheet and the information it contains is believed to be accurate as of the date of creation. Please email [technical@rockoil.co.uk](mailto:technical@rockoil.co.uk) or telephone +44 (0) 1925 636191 if you require any further information.