



TECHNICAL DATA SHEET

STRAWBERRY 2 STROKE

Strawberry 2 Stroke is a low ash synthetic two-stroke lubricant with a sweet strawberry fragrance for use in injection systems or as a pre-mix at the manufacturer's recommended ratios.

FEATURES

- Low ash formulation provides high resistance to harmful pre-ignition, a severe problem in larger or more powerful two-stroke engines.
- Ultimate protection for today's high performance two-stroke throughout a very wide temperature range.
- Benefits include; accurate metering, sharp throttle response, low smoke and extreme thermal stability.
- Maximum performance, even under the most severe conditions.
- The synthetic formulation helps provide maximum shear strength for complete protection of crankshafts and pistons and improved engine cleanliness, and reduced smoke.

PERFORMANCE SPECIFICATIONS, APPROVALS & RECOMMENDATIONS:

JASO FC, FD

ISO-L-EGD

Strawberry Trial 2 Stroke also meets the requirements of SEA-DOO jet skis.

TYPICAL PHYSICAL CHARACTERISTICS

Density @ 15°C	0.867
Viscosity @ 40°C	61.0 cSt
Pour Point	< - 20°C
Appearance	Clear red liquid
Product Code	07200

This data sheet and the information it contains is believed to be accurate as of the date of creation. Please email technical@rockoil.co.uk or telephone +44 (0) 1925 636191 if you require any further information.