



TECHNICAL DATA SHEET

KOOL-GUARD™ MEG -38

A high-performance mono-ethylene glycol-based ready-to-use engine coolant. It employs established IAT (Inorganic Acid Technology) inhibitor technology and is nitrite, amine and phosphate (NAP) free. It includes borates and silicates.

FEATURES

- Containing a balanced mixture of effective corrosion inhibitors formulated to give outstanding corrosion protection whether the system is of predominantly aluminium or ferrous material
- Universal product suitable for a wide range of engines such as cars, motorcycles, trucks, buses, coaches and off-road equipment used in agriculture, construction, mining and power generation.
- Year-round treatment providing protection against winter freezing, overheating and corrosion

PERFORMANCE SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

AFNOR	NF R15-601
AS	2108:2004
ASTM	D3306
BS	6580:2010
BTC CLASSIFICATION	TYPE 2E
CUNA	NC 956-16
FVV	Heft R443
ONORM	V 5123
SAE	J1034
UNE	26-361

TYPICAL PHYSICAL CHARACTERISTICS

Density @ 20°C	1.075
Freezing Point	-38°C
Appearance	Clear blue liquid
Product Code	08650

This data sheet and the information it contains is believed to be accurate as of the date of creation. Please email technical@rockoil.co.uk or telephone +44 (0) 1925 636191 if you require any further information.

Copyright © Rock Chemicals Ltd T/A Rock Oil & Rock Oil Co. Rock Oil®, and the R Rock Oil logo® are registered trademarks of Rock Chemicals Ltd. KOOL-GUARD is a trademark of Rock Chemicals Ltd. All other trademarks, trade names, and copyrights mentioned are the property of their respective owners.