



# TECHNICAL DATA SHEET

## DOT 4 UNIVERSAL BRAKE AND CLUTCH FLUID

DOT 4 is a high quality brake and clutch fluid, blended from superior materials to a high standard of purity.

### FEATURES

- Suitable for use in all motor vehicles and motorcycles made in the UK, USA, Europe and Japan
- It cannot be used in Citroen or other vehicles requiring mineral based fluids
- Mixes safely with the SAE J1703, DOT 3 and DOT 4 brake fluids

### PERFORMANCE SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

SAE	J1703, SAE J 1704
US FMVSS 116	DOT 4 AND DOT 3
ISO	4925

### CAUTION:

- Brake fluid can damage vehicle paintwork and it must be washed off with water immediately. It is also necessary to keep the container tightly sealed to prevent absorption of moisture.
- Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs.

### TYPICAL PHYSICAL CHARACTERISTICS

Density @ 20°C	1.050
Equilibrium reflux boiling point	243 °C
Wet equilibrium boiling point	160 °C
Viscosity @ -40°C	1296 cSt
Viscosity @ 100°C	2.17 cSt
Appearance	Clear Pale Amber Liquid
Product code	14420

This data sheet and the information it contains is believed to be accurate as of the date of creation. Please email [technical@rockoil.co.uk](mailto:technical@rockoil.co.uk) or telephone +44 (0) 1925 636191 if you require any further information.