



TECHNICAL DATA SHEET

WHITE SPRAY GREASE

A high-quality multi-purpose grease enhanced with a specially selected water-repellent additive for use in applications requiring extreme water resistance. Used extensively for applications throughout industry, marine and the automotive sector in anti-friction and plain bearings and pumping equipment where water ingress can be detrimental to lubrication.

FEATURES

- Versatile multi purpose grease
- Excellent water resistance
- Excellent corrosion protection
- Good sealing properties

TYPICAL PHYSICAL CHARACTERISTICS

Appearance	Smooth grease
Colour	Off white
NLGI classification	2
Thickener	Lithium soap
Base oil	Mineral oil
Base oil viscosity @ 40°C (IP71) cSt	110
Worked penetration (IP50)	265 to 295
Dropping point (IP132) °C	185 min.
Oil separation (IP121) %	5 max.
Copper corrosion (IP112)	Pass
Resistance to corrosion Emcor (IP 220)	0:0
Water washout (ASTM D1264) @ 39°C %	2
@79°C %	4
Oxidation stability @ 100°C (IP142)	
Pressure drop after 100 hrs psi	4
Zinc oxide content %	10
Operating temperature range	-20°C to +140°C
Product Code	64040

This data sheet and the information it contains is believed to be accurate as of the date of creation. Please email technical@rockoil.co.uk or telephone +44 (0) 1925 636191 if you require any further information.