



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture Ultra 2-Step Finishing Polish

Registration number -

Synonyms None.

Product Code 1394

Issue date 06-30-2015

Version number 02

Revision date 07-21-2015

Supersedes date 06-30-2015

Distributor in New Zealand

Pacer Car Clean Products NZ LTD
33 Ha Crescent Wiri
Auckland, New Zealand
Telephone: +64 9 25000 91
Fax: +64 9 25000 92
Web: :www.pacer.co.nz

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Compound, Polishing Creme

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name Presta Products

Address 361 Fairview Ave
Barberton, OH 44203
US

Division

Telephone Phone 800-253-2526
Fax 330-777-8317

e-mail msdsinfo@malcopro.com

Contact person Not available.

1.4. Emergency telephone number Phone 1-800-424-9300

24hr Emergency Assistance in New Zealand

National Poison Control Center: 0800 Poison [764 766]

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Specific target organ toxicity - repeated exposure Category 2

H373 - May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Category 1

H304 - May be fatal if swallowed and enters airways.

Hazard summary Combustible. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. Occupational exposure to the substance or mixture may cause adverse health effects.

Hazard Summary (according to Dangerous Substances Directive)

Physical hazards Not classified for physical hazards.

Health hazards Not classified for health hazards.

Environmental hazards Not classified for hazards to the environment.

Specific hazards None known.

Main symptoms Aspiration may cause pulmonary edema and pneumonitis. Prolonged exposure may cause chronic effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Solvent Naphtha (Petroleum), Medium Aliph.

Hazard pictograms



Signal word

Danger

Hazard statements

H304

May be fatal if swallowed and enters airways.

H373

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention

P260

Do not breathe mist or vapor.

Response

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P314

Get medical advice/attention if you feel unwell.

P331

Do NOT induce vomiting.

Storage

P405

Store locked up.

Disposal

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards Combustible.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (Petroleum), Hydrotreated Light	10 - < 20	64742-47-8 265-149-8	-	649-422-00-2	
Classification:	Asp. Tox. 1;H304				
Solvent Naphtha (Petroleum), Medium Aliph.	5 - < 10	64742-88-7 265-191-7	-	649-405-00-X	
Classification:	Asp. Tox. 1;H304, STOT RE 1;H372				

Other components below reportable levels 80 - < 90

List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Combustible. No unusual fire or explosion hazards noted.
5.1. Extinguishing media	
Suitable extinguishing media	Powder. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	Cool containers exposed to heat with water spray and remove container, if no risk is involved.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Do not breathe mist or vapor. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat and sources of ignition. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	MAK	5 mg/m ³	Respirable fraction.
		5 mg/m ³	Respirable fume.
		10 mg/m ³	Inhalable fraction.
	STEL	20 mg/m ³	Inhalable fraction.
		10 mg/m ³	Respirable fume.
		10 mg/m ³	Respirable fraction.

Belgium. Exposure Limit Values.

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	1 mg/m ³	Respirable fraction.
Glycerol (CAS 56-81-5)	TWA	10 mg/m ³	Mist.

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work			
Components	Type	Value	Form
Aluminum Silicate (CAS 66402-68-4)	TWA	6 mg/m ³	Inhalable fraction.
		3 mg/m ³	Respirable fraction.
Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	MAC	4 mg/m ³	Respirable dust.
		10 mg/m ³	Total dust.
Glycerol (CAS 56-81-5)	MAC	10 mg/m ³	
Czech Republic. OELs. Government Decree 361			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	0,1 mg/m ³	Respirable dust.
	Ceiling	15 mg/m ³	Mist.
Glycerol (CAS 56-81-5)	TWA	10 mg/m ³	Mist.
Denmark. Exposure Limit Values			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TLV	5 mg/m ³	Total
		2 mg/m ³	Respirable.
Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	4 mg/m ³	Respirable dust.
		10 mg/m ³	Total dust.
Glycerol (CAS 56-81-5)	TWA	10 mg/m ³	
Finland. Workplace Exposure Limits			
Components	Type	Value	Form
Glycerol (CAS 56-81-5)	TWA	20 mg/m ³	
France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	VME	10 mg/m ³	
Glycerol (CAS 56-81-5)	VME	10 mg/m ³	Aerosol.
Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	4 mg/m ³	Inhalable dust.
		1,5 mg/m ³	Respirable dust.
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	140 mg/m ³	Vapor and aerosol.
		20 ppm	Vapor and aerosol.
Glycerol (CAS 56-81-5)	TWA	50 mg/m ³	Inhalable fraction.
Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	AGW	10 mg/m ³	Inhalable fraction.
		1,25 mg/m ³	Respirable fraction.
Greece. OELs (Decree No. 90/1999, as amended)			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	5 mg/m ³	Inhalable
		10 mg/m ³	Respirable.
Glycerol (CAS 56-81-5)	TWA	10 mg/m ³	

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	6 mg/m3	Respirable.
Iceland. OELs. Regulation 154/1999 on occupational exposure limits			
Components	Type	Value	
Calcined Alumina (CAS 1344-28-1)	TWA	10 mg/m3	
Ireland. Occupational Exposure Limits			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Mist.
Latvia. OELs. Occupational exposure limit values of chemical substances in work environment			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	6 mg/m3	Decomposition aerosol.
		4 mg/m3	
Norway. Administrative Norms for Contaminants in the Workplace			
Components	Type	Value	
Calcined Alumina (CAS 1344-28-1)	TLV	10 mg/m3	
Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	2,5 mg/m3	Fume, total dust.
		1,2 mg/m3	Respirable dust and/or fume.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Aerosol.
Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)			
Components	Type	Value	
Calcined Alumina (CAS 1344-28-1)	TWA	10 mg/m3	
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	
Romania. OELs. Protection of workers from exposure to chemical agents at the workplace			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	STEL	5 mg/m3	Aerosol.
		1,2 ppm	Aerosol.
	TWA	2 mg/m3	Aerosol.
		0,5 ppm	Aerosol.
Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	4 mg/m3	Inhalable fraction.
		1,5 mg/m3	Respirable fraction.
		0,1 mg/m3	
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	
Spain. Occupational Exposure Limits			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	10 mg/m3	
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Mist.
Sweden. Occupational Exposure Limit Values			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	5 mg/m3	Total dust.

Sweden. Occupational Exposure Limit Values

Components	Type	Value	Form
		2 mg/m3	Respirable dust.
Switzerland. SUVA Grenzwerte am Arbeitsplatz			
Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	STEL	24 mg/m3	Fume and respirable dust.
	TWA	3 mg/m3	Respirable dust.
		3 mg/m3	Fume and respirable dust.
Glycerol (CAS 56-81-5)	STEL	100 mg/m3	Inhalable dust.
	TWA	50 mg/m3	Inhalable dust.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Mist.

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no-effect level (DNEL) Not available.

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

- Other Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.
 Form Liquid. Viscous.
 Color Light grey

Odor Pina Colada

Odor threshold Not available.

pH 8,5

Melting point/freezing point 2741 °F (1505 °C) estimated

Initial boiling point and boiling range 4185,5 °F (2307,5 °C) estimated

Flash point 145,0 °F (62,8 °C)

Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	0,06 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Solubility (other)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	739 °F (392,78 °C) estimated
Decomposition temperature	Not available.
Viscosity	20000 cP
Viscosity temperature	68 °F (20 °C)
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
9.2. Other information	
Density	8,67 lbs/gal
Kinematic viscosity	31853 cSt
Kinematic viscosity temperature	68 °F (20 °C)
VOC (Weight %)	5 % By Weight

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Acids. Strong oxidizing agents. Chlorine.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
Information on likely routes of exposure	
Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms	Aspiration may cause pulmonary edema and pneumonitis.
11.1. Information on toxicological effects	
Acute toxicity	May be fatal if swallowed and enters airways.
Skin corrosion/irritation	Due to partial or complete lack of data the classification is not possible.
Serious eye damage/eye irritation	Due to partial or complete lack of data the classification is not possible.
Respiratory sensitization	Due to partial or complete lack of data the classification is not possible.
Skin sensitization	Due to partial or complete lack of data the classification is not possible.
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.
Carcinogenicity	Due to partial or complete lack of data the classification is not possible.

Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Mixture versus substance information	No information available.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)		
Aquatic Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	2,9 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment Not available.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

ADN

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

New Zealand ERMA Register of Hazardous Substances HSNO: HSR002525 Cleaning products (Combustible) Group Standard 2006

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended
Not listed.
- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II, as amended
Not listed.
- Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended
Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended
Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended
Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended
Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended
Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended
Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA
Not listed.

Authorizations

- Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended
Not listed.
- Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended
Not listed.

Restrictions on use

- Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended
Not listed.
- Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended
Not listed.
- Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended
Not listed.

Other EU regulations

- Directive 2012/18/EU on major accident hazards involving dangerous substances
Not listed.
- Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)
Solvent Naphtha (Petroleum), Medium Aliph. (CAS 64742-88-7)
- Directive 94/33/EC on the protection of young people at work, as amended
Solvent Naphtha (Petroleum), Medium Aliph. (CAS 64742-88-7)

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15 H304 May be fatal if swallowed and enters airways.

Revision information**Training information****Disclaimer**

H372 Causes damage to organs through prolonged or repeated exposure.

This document has undergone significant changes and should be reviewed in its entirety.

Follow training instructions when handling this material.

Presta Products cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.