

TECHNICAL DATA SHEET

Phone: (09) 25000 91

ACETONE

DESCRIPTION:

Acetone is a very fast drying solvent used in paint removers, paint thinners, adhesives and in the manufacture of fiberglass.

DIRECTIONS:

Cleaning: Spray onto the surface, agitate to clean and then wipe off with a clean cloth or allow to evaporate.

Warning! This is a professional grade product for use by professional, trained personnel with an awareness of hazard and safety procedures. Not for use by the general public.

APPLICATIONS:

Paint thinners, Solvent, Cleaner.

PROPERTIES:

Colourless liquid with characteristic odour.

Available Sizes:







ACE20

DANGER

CAS Number 67-64-1 Flammable Liquid Category 2 Acute Oral Toxicity Category 4

H225 Highly flammable liquid and vapour

H302 Harmful if swallowed

H304 May be fatal if swallowed and enters airways















DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOUR. Harmful if swallowed. Aspiration into the lungs may cause chemical Pneumonitis, which can be fatal. Causes serious eye irritation. Causes mild skin irritation. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. Continued inhalation may result in unconsciousness and/or death.

SAFETY PRECAUTIONS: Keep well away from heat, sparks and open flame. Keep container well closed. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protections. Do not eat, drink or smoke whilst using. Avoid breathing vapour. Use with adequate ventilation. Dispose empty container in a safe manner.

FIRST AID:

Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyes open. Transport to the nearest medical facility for additional treatment. Skin Remove contaminated clothing. Flush exposed area with water and follow up by washing with soap if available.

Ingestion If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Inhalation Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

If medical advice is needed have the product container/label at hand. In an emergency phone the National Poison Centre. (24 hrs): 0800 POISON[764 766]. Contains 100% Acetone. UN 1090. Class 3. PG II. Hazchem 3[Y].

OUR VISION AND MISSION

To be the leading value-based provider to the market. We have a dedicated team to achieve excellence for our customers and a philosophy of total quality. We conduct business and create relationships in an ethical and sustainable manner with customers, our community and the environment. The value we provide our customers is the opportunity to increase profit through lower cost solutions that do not sacrifice quality or service.

ENVIRONMENTAL POLICY

Pacer is committed to leading the industry in minimising the impact of its activities on the environment. The key points of our strategy to achieve this are: Purpose built premises utilising energy efficient technology and rain water collection. Actively promoting recycling both internally and amongst our customers and suppliers. To develop and promote a product range to minimise the environmental impact of our products. We are constantly evaluating and looking at substituting to a more environmentally friendly composition of raw materials for our products. To meet or exceed all the environmental legislation that relates to our industry.

DISCLAIMER

The technical data and information provided, including the recommendations for applying & using our products, is given in good faith based on our current knowledge and experience and is believed to be accurate when applied under 'normal' conditions. In practice, the materials, surfaces or conditions are so varied that no warranty regarding the working results or any liability or guarantee can be inferred either from this information nor from a verbal consultation. It is recommended that the user makes his or her own tests to determine the suitability of the product for their own requirements.