

# TYPE PAINT SATIN

**TECHNICAL DATA SHEET** 

Phone: (09) 25000 91 Fax: (09) 25000 92 Email: sales@pacer.co.nz

## **DESCRIPTION:**

Tyre Paint Satin is a fast drying mineral based paint designed to be used on tyres to provide a satin finish. Tyre Paint Satin has excellent flexibility and durability.

# **DIRECTIONS:**

Shake well. The surface should be clean and dry, free of dirt, silicone and any contamination. Apply Tyre Paint Satin with a paintbrush and allow to dry. If necessary thin with Mineral Turpentine.

# **APPLICATIONS:**

Tyre paint

## **PROPERTIES:**

Black liquid with a flash point of 38°C

#### **Available Sizes:**







**TPS20** 

#### **DANGER**

H304 May be fatal if swallowed and enters airways H312 Harmful in contact with skin H332 Harmful if inhaled





















DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOUR. May be fatal if swallowed and enters airways. Aspiration into the lungs may cause chemical pneumonitis which can be fatal. May cause transitory pain to eyes. Harmful in contact with skin. Harmful if inhaled. May cause headache dizziness, nausea, and narcosis

SAFETY PRECAUTIONS: Keep away from sparks/open flames. No smoking. Keep container tightly closed. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Wash hands thoroughly after handling. Avoid release to the environment. Store in a well-ventilated place. Keep cool.

#### FIRST AID:

Flush with cold water for at least 15 minutes. Seek medical attention if problems persists.

Skin If skin contact causes irritation remove contaminated clothing and wash thoroughly with soap and water.

Ingestion Do not induce vomiting. Give nothing by mouth. If patient continues to be distressed seek medical attention immediately.

Inhalation Remove to fresh air. If breathing is difficult seek medical attention immediately.

If medical advice is needed have the product container/label at hand. In an emergency phone the National Poison Centre. (24 hrs.): 0800 POISON[764 766].

# UN 1993. Class 3. PG III. Flammable Liquid N.O.S.

**OUR VISION AND MISSION** To be the leading value-based provider to the market. We have a dedicated team to achieve excellence for our customers and a philosophy of total quality. We conduct business and create relationships in an ethical and sustainable manner with customers, our community and the environment. The value we provide our customers is the opportunity to increase profit through lower cost solutions that do not sacrifice quality or service.

# **ENVIRONMENTAL POLICY**

Pacer is committed to leading the industry in minimising the impact of its activities on the environment. The key points of our strategy to achieve this are: Purpose built premises utilising energy efficient technology and rain water collection. Actively promoting recycling both internally and amongst our customers and suppliers. To develop and promote a product range to minimise the environmental impact of our products. We are constantly evaluating and looking at substituting to a more environmentally friendly composition of raw materials for our products. To meet or exceed all the environmental legislation that relates to our industry.

#### **DISCLAIMER**

The technical data and information provided, including the recommendations for applying & using our products, is given in good faith based on our current knowledge and experience and is believed to be accurate when applied under 'normal' conditions. In practice, the materials, surfaces or conditions are so varied that no warranty regarding the working results or any liability or guarantee can be inferred either from this information nor from a verbal consultation. It is recommended that the user makes his or her own tests to determine the suitability of the product for their own requirements