

## STANDARD NYLON CABLE GLANDS

### Application

Remtek's standard range of Nylon Glands are a unique product. A camera shutter principle in the cable sealing mechanism makes the gland 50m submersible. There is no need to disassemble the gland prior to installation - just insert the cable through and tighten up. The cable diameter range that each gland can take is large, thus reducing stock inventories.

### Features

- Complete with rubber gasket
- Large cable range
- Strain relief
- UV Stabilised
- Metric thread complete with lock and nut
- Vibration resistant - Ratchet action
- IP68 Rating

Nylon Cable Gland - RNG



Metric Gland Range					
Part No.	Cable Thread Size	Length Range O.D (mm)	Width of Thread (mm)	A/F (mm)	Std Pack
<b>RNG12</b>	M12	3-6.5	8	15.0	50
<b>RNG16</b>	M16	5-10	15	21.8	50
<b>RNG20</b>	M20	10-14	15	26.3	36
<b>RNG25</b>	M25	13-18	15	32.0	16
<b>RNG32</b>	M32	18-25	15	41.5	12
<b>RNG40</b>	M40	22-32	18	49.2	6
<b>RNG50</b>	M50	30-38	18	59.2	3
<b>RNG63</b>	M63	34-44	18	71.2	2

Metric glands supplied complete with locknut and body seal.

Get in touch with our sales team for a quote on your next project

Phone 03 9312 6633

**G.V.Kinsman PTY LTD**

660 Somerville Rd, Sunshine West  
Victoria, 3020

Web..... [www.gvk.com.au](http://www.gvk.com.au)

Email..... [sales@gvk.com.au](mailto:sales@gvk.com.au)

Phone..... 03 9312 6633

Fax..... 03 9312 6433