



SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: Mag Wheel Cleaner

Product Code: MWC

Product Use: To remove brake dust, road film, oxidation and dirt from

non-painted mag wheels and aluminum boats

New Zealand Supplier: Car Clean Products NZ Limited

Address: 33 Ha Crescent

Wiri Auckland

Telephone: 09 250 0091 Fax Number: 09 250 0092

Emergency Telephone: 0800 POISON (0800 764 766)

Date of MSDS Preparation: March 2022

Section 2. Hazards Identification

Potential Health Effects

Hydrofluoric acid solutions are toxic and corrosive. Every care must be taken to ensure that this product does not come into contact with eyes. Skin must be washed with soapy water immediately after any contact.

The antidote for hydrofluoric acid poisoning is calcium gluconate as a gel or tablets. The concentration in this product is sufficiently low that this should not be necessary. However it is wise to have the antidote on hand if extensive skin contact could occur.







DANGER

H301 Toxic if swallowed

H311 Toxic if contact with skin

H314 Causes serious skin burns and eye damage

H370 Causes damage to organs

Swallowed Liquid is corrosive to mucous membranes

Eyes Extremely irritating can cause severe burns and prolonged or

permanent loss of sight

Skin Extremely irritating to skin can cause immediate burns.

Pain may not be noticed for some hours. In extreme cases skin is readily penetrated causing liquefaction necrosis of the soft tissues

and decalcification of the bone

Inhalation Vapour is corrosive and irritating to the respiratory tract. Exposure

to high concentrations may cause bronchitis

Section 3. Composition / Information on Ingredients

| Ingredients | Proportion (% mass) | Cas No |
|---------------------------------|---------------------|-----------|
| Water | <80 | 7732-18-5 |
| Alkylsulfonic Acid | <10 | 75-75-2 |
| Hydrofluoric Acid | <1 | 7664-93-3 |
| Nonylphenol ethoxylate | <1 | 9016-45-9 |
| Ethylene Glycol monobutyl ether | >1 | 111-76-2 |

Section 4. First Aid Measures

Routes of Exposure:

Eye Hold eyes open and flush with water for at least 15 minutes. Seek

medical attention immediately. TAKE THIS SDS or CONTAINER

Skin Immediately remove contaminated clothing and wash skin and

clothes thoroughly with soap and water. Treat immediately with

calcium gluconate antidote gel

Ingestion Do not induce vomiting. Give large quantity of milk or water. Seek

medical attention immediately. TAKE THIS SDS or CONTAINER.

Inhalation Remove to fresh air. If breathing is difficult, seek medical

attention immediately

Section 5. Fire Fighting Measures

Suitable Extinguishing media Dry Chemical powder

Fire and Explosion hazards
Non combustible liquid but will form corrosive vapour

Fire Fighting Instructions

Fire fighters must use recommended protective equipment and self-contained breathing apparatus.

Hazchem Code 2X

Section 6. Accidental Release Measures

Land Spill or Leaks Wear protective gloves and goggles and protect exposed

skin. Remove unprotected personnel from the area. Contain spill with sand, earth or vermiculite. Transfer to a waste container. Label container as hazardous waste,

toxic and corrosive, for approved disposal.

Water Small spills and leaks should not pose any long term

effects to aquatic environment. Large spills should be advised to the nearest regional council pollution officer to

assist with containment and remediation.

Section 7. Handling and Storage

Handling Advice For normal label use it is advisable to wear goggles and

gloves. For bulk handling and transfer use a full-face

mask, gloves, and safety gumboots.

Storing Procedures Store away from heat and direct sunlight. Do not store next

to food or feedstuffs. Check regularly for leaks.

Ensure adequate ventilation. Keep out of reach of

children.

Section 8 Exposure Controls / Personal Protection

Engineering Controls: Use in well ventilated area. Ensure containers have

hazardous labels.

Personal Protective Equipment: Advisable to wear PVC or Viton gloves for normal label

use. For bulk use and transfer also wear SAA approved

acid vapour respirator and PVC safety gumboots.

Section 9 Physical and Chemical Properties

Appearance Pale Green liquid
Odour: Sharp, acidic
Odour threshold Data not available

pH: <1

Melting/Freezing point Data not available Initial boiling point/range Data not available

Flash point N/A

Flammability N/A Upper/Lower flammability limits N/A

Vapour pressure Data not available Vapour density Data not available Relative density Data not available

Solubility in water: 100%

Partition coefficient Data not available

Auto-ignition temperature N/A

Decomposition temperature Data not available Kinematic viscosity Data not available Particle characteristics Data not available

Section 10. Stability and Reactivity

Chemical Stability Stable, but will give off corrosive vapour

Conditions to Avoid High temperatures

Incompatibility Metals and strong alkalis

Hazardous Decomposition

Products Can form hydrogen in the presence of zinc or aluminium.

Toxic fumes in a fire.

Section 11 Toxicological Information

Acute Inhalation Toxicity LC₅₀ Mouse (inhalation) 4Hour 14mg/L air

Long term Effects Insufficient information is available to establish any

chronic effects

Toxicological Data Insufficient information available

Section 12. Ecotoxicological Information

Environmental Precautions:

Ecological Toxicity Toxic to all forms of marine organisms, terrestrial

vertebrates and invertebrates.

Environmental Fate:

Soil Biodegradable, not likely to persist

Water Biodegradable, not likely to persist

Section 13. Disposal Considerations

Dispose of waste at an appropriate waste disposal facility in accordance with local authority bylaws

Product Name: Mag Wheel Cleaner Copyright© Car Clean Products NZ Ltd

Date of SDS: March 2022

Section 14 Transport Information

Road, Rail, Marine and Air Transport
UN No 3264
Class-primary 8
Packing Group III

Proper Shipping Name Corrosive liquid acid inorganic N.O.S. (dilute hydrofluoric

acid)

Section 15 Regulatory Information

HSNO Classification Acutely toxic class 6.1D,

Toxic to human target organs 6.9A (oral and inhalation),

Corrosive to metals 8.1A Corrosive to skin 8.2C Corrosive to eye 8.3A

Ecotoxic to terrestrial vertebrates 9.3B

Group Standard Cleaning Products (Corrosive)

ERMA Approval No HSR002526

Section 16 Other Information

Supplied in 1lt, 4lt, 20lt containers. Code: MWC1, MWC4, MWC20.

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand proprietor, Car Clean Products NZ Limited, Phone: 09 250 0091, if further information is required.



MAG WHEEL CLEANER

PURPOSE:

Mag Wheel Cleaner is a powerful blend of acids and detergents formulated to remove brake dust, road film, oxidation and dirt from older mag wheels and aluminum boats.

CAUTION:

Do **NOT** use on clear coated, anodized, chrome, painted, plastic or any other kind of coated surface. Use **ONLY** on alloy, aluminum and magnesium surfaces.

DIRECTIONS:

Dilute 1 part Mag Wheel Cleaner to 10 parts water. Spray onto surface and allow a few minutes to react. Agitate with a brush and rinse thoroughly with water. Repeat the process if necessary.

WARNING:

Corrosive to human tissue. Harmful if swallowed, inhaled or absorbed through the skin. May cause burns to skin and eyes.

KEEP OUT OF REACH OF CHILDREN.