



SUPREME

CLEANING PRODUCTS

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: Rubber Restorer
Recommended Use: Restoring and protecting rubber plastic and vinyls.

Supplier: SUPREME CLEANING PRODUCTS
Address: 65 Maleme street Greerton Tauranga

Telephone:
Facsimile: (+64) 7 541 0390
Website: (+64) 7 541 1864
www.supremecleaning.co.nz

Emergency phone:
National Poisons Centre
0800 POISON [0800 764 766]

2. HAZARDS IDENTIFICATION

Product is classified as hazardous according to Schedules 1 to 6 of the *Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001* of the HSNO Act, 1996.

HSNO Classifications: 3.1C, 6.1E, 6.3B, 6.7B, 6.8B, 6.9B, 9.1B



Signal word: DANGER

Hazard Statements:

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H316 Causes mild skin irritation.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long-lasting effects.

Prevention Statements :

P102 Keep out of reach of children.
P103 Read label before use.

Product : Rubber Restorer
Date of Issue: 29th March 2024

Page 1 of 8



SUPREME

CLEANING PRODUCTS

- P201 Obtain special instructions before use.
P202 Do not handle until all safety instructions have been read and understood.
P210 Keep away from heat, open flames, hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond containers and receiving equipment.
P241 Use explosion proof electrical/ventilating/lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe vapours.
P273 Avoid release to environment.
P280 Wear protective gloves and eye protection.

Response Statements:

- P101 If medical advice is needed, have product container or label at hand.
P314 Get medical advice if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice.

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor.
P331 Do NOT induce vomiting.

- P303 + P361 + P353 IF ON SKIN (or hair): remove immediately all contaminated clothing.
Rinse skin with water.

- P332 + P313 If skin irritation occurs: Get medical advice.

- P370 + P378 In case of fire: Stop leak if safe to do so.

- P391 Collect spillage.

Storage Statements:

- P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal Statements:

- P501 Dispose of product and containers in accordance with local regulations.

3. COMPOSITION : Information on Ingredients

Chemical Ingredient	CAS No.	Proportion (%)
Low aromatic solvent	64742-82-1	60-80%
Ballance non hazadous		

4. FIRST AID MEASURES

For advice, contact National Poisons Centre (0800 POISON; 0800 764 766) or a doctor.
Have product container or label available.

Swallowed

If swallowed, do NOT induce vomiting. Rinse mouth. Get medical attention. If spontaneous vomiting occurs, hold patients head below hips to avoid possible aspiration of vomitus into lungs.

Skin Contact

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, get medical attention.

Eye Contact

Hold eyelids apart and flush the eye continuously with running water. Continue flushing for at least 15 minutes. Remove contact lenses if present and easy to do, after the first 5 minutes and continue rinsing. Get medical attention if irritation persists.

Inhalation

Move the victim to fresh air immediately. Keep warm and at rest until recovered. Get medical attention if recovery is not rapid.

First Aid Facilities: Provide eye bath and hand washing facilities.

Advice to Doctor: Treat according to symptoms. Risk of aspiration into lungs with potential to cause chemical pneumonitis.

5. FIRE FIGHTING MEASURES

Flashpoint: 41- 42°C

Flammable limits: LFL : 0.7% UFL: 6.5%

Extinguishing media:

Foam, CO₂ or dry chemical. Use water spray or water fog on large fires only.

Fire & Explosion hazards:

Flammable liquid and vapour. The vapour forms explosive mixtures with air. Do not breathe smoke, gases or vapours generated in a fire. Decomposition products may be toxic.

Firefighting Equipment:

Full protective clothing and self-contained breathing apparatus (SCBA).

In event of fire:

- Alert Fire Bridge (111); advise location and nature of hazard.
- Keep bystanders away.
- Wear breathing apparatus and protective gloves.
- Shut off product that may 'fuel' a fire if safe to do so.
- Eliminate sources of ignition
- If safe, switch off electrical equipment until vapour hazard removed.
- Use fine water spray to control fire and cool adjacent area.
- Allow trained personnel to attend a fire in progress, providing fire-fighters with this Safety Data Sheet.
- Prevent product and extinguishing media from escaping to drains and waterways.

Hazards from combustion products:

Product will emit toxic fumes of carbon monoxide and carbon dioxide.

Hazchem Code: 3Y

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures & Containment:

Refer to “Fire Fighting Measures”, “First Aid Measures” and “Stability and Reactivity”.

Minor spills

- Clean up spills immediately.
- Remove all ignition sources.
- Avoid breathing vapours and contact with skin and eyes.
- Wear personal protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Collect residues and waste material in a labelled container.
- Seal container and dispose of safely.

Major spills

- Clear area of personnel and move upwind.
- Alert Fire Bridge (111); advise location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Eliminate ignition sources, naked lights. No smoking.
- Stop leak if safe to do so.
- Water spray or water fog may be used to disperse or absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use spark-free shovels and explosion proof equipment.
- Prevent by any means available, spillage from entering drains, sewers, watercourses, or low-lying areas.
- Increase ventilation.
- Collect recoverable product into labeled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent run off into drains.
- If contamination of drains or waterways occurs, advise Emergency Services and Local or Regional authority.

7. HANDLING AND STORAGE

Precautions for safe handling:

Read product label before use. Use in a well-ventilated area. Avoid smoking, naked lights or ignition sources. Avoid generation of static electricity. Do NOT use plastic buckets. Use only spark-free tools. Avoid all personal contact including by inhalation. Wear personal protective equipment and clothing including gloves and wash hands with soap and water after handling.

Conditions for safe storage:

Store locked up in original packaging in a cool, dry well-ventilated place out of reach of children. Check containers periodically for leaks or distortion.

Incompatible materials:

Natural rubber, butyl rubber, nitrile rubber, EPDM, polystyrene.

8. EXPOSURE CONTROLS : PERSONAL PROTECTION

Health Exposure Standards:

Workplace Exposure Standards (WES) have been set for a similar product and a component in this product.

	WES-TWA	WES-STEL
White spirits (Stoddard solvent)	100 ppm (525 mg/m ³)	-
Ethylbenzene	100 ppm (434 mg/m ³)	125 ppm (543 mg/m ³)

Biological limit values: None established

Engineering Controls:

Ventilation: Avoid breathing vapours. Use product outdoors or in well-ventilated area.

Personal Protective Equipment:

Respiratory Protection: Not normally required. Where the air concentration may exceed the Workplace Exposure Standard, wear SAA approved respiratory protection. A half-filter mask and type 'A' filter material should be suitable.

Eye Protection: Protect eyes from splashes. Always use safety glasses with side shields, or wear goggles.

Skin/ Body Protection:

Wear gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. chemical resistant rubber, and clothing with long sleeves and long trousers or coveralls.

9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value
Appearance	-	Clear colourless liquid
Odour	-	Solvent (paraffinic)
Flash Point	°C	41 - 42 °C
Autoignition temperature	°C	296
Specific gravity @ 20°C	g/ml	0.78 – 0.79
Vapour Pressure @ 20°C	Pa	370
Vapour Density @ 20°C	kPa	Not available
Explosive Limits in Air	%	0.7 – 6.5
Viscosity	cSt	Not available
Volatiles	%vol/vol	100
Alkalinity/acidity (as pH)	-	Not applicable
Solubility in Water	% w/w	Immiscible

The values listed are indicative of this product's physical and chemical properties.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at room temperature and pressure.
Conditions to avoid: Sources of heat, ignition, open flames and contact with oxidizing agents.
Hazardous decomposition products: No decomposition products except on burning.
 See "Fire Fighting Measures" and "Hazardous Reactions".
Hazardous reactions: With oxidizing agents

11. TOXICOLOGICAL INFORMATION

Acute Effects

Ingestion

Swallowing small amounts or from vomiting may cause aspiration into lungs and cause chemical pneumonitis or pulmonary edema. If swallowed, symptoms may include headaches, nausea, dizziness and tracheal burning.

Eye Contact

This product may be irritating to the eyes resulting in tearing and redness but will not permanently damage eye tissue.

Skin Contact

This product can be moderately irritating to the skin. Prolonged or repeated exposure may defat skin leading to drying, cracking and possibly non-allergenic contact dermatitis.

Inhalation

Vapours may cause discomfort or irritation to the upper respiratory tract. Symptoms of over-exposure may be coughing, choking, wheezing, difficulty in breathing, drowsiness and dizziness.

Chronic Effects: Repeated or prolonged exposure by inhalation to mixed hydrocarbons may result in dizziness, weakness, irritability, lack of concentration and memory loss, tremor of extremities, e.g. fingers, weight loss, anemia, ill-effects to liver and kidneys. Auditory system effects may include temporary hearing loss and/or ringing in the ears.

Other Health Effects Information: This product contains $\geq 0.3\%$ ethyl benzene which is classified as both a suspected carcinogen and suspected of damaging fertility or the unborn child. In addition, 1,2,4-trimethyl benzene is classified as may cause damage to organs through prolonged or repeated exposure.

Toxicological Information:

1,2,4-Trimethyl benzene Oral, LD₅₀, rat 3280 mg/kg
 Inhalation, LC₅₀ (4hr), rat 18 mg/L

12. ECOLOGICAL INFORMATION

Do not discharge product to sewer, drains or waterways.

Ecotoxicity:

Aquatic toxicity: This product has been classified as being toxic to aquatic life with long-term effects.

Persistence/degradability: Not expected to be persistent or bioaccumulative. However, contains components that may not be readily biodegradable. Degrades rapidly in air.

Mobility: Product is not miscible with water however is highly mobile in soil and may contaminate groundwater. Product is highly volatile and will evaporate to air.

Other information: Not available.

Environmental Exposure Standards: Not set.

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national, regional and local authority regulations. Packaging may still contain product vapours. Allow container to dry before disposal. Do not use container for storing other products.

Dispose of product through waste management facility for solvent recovery or disposal, e.g. by incineration.

14. TRANSPORT INFORMATION

UN Number: 1268
Shipping name: Rubber Restorer
Class: 3
Packing group: III
Hazchem code: 3Y

Dangerous Goods Segregation

This product is classified as Dangerous Good Class 3.

Please consult NZS 5433:2012 Transport of Dangerous Goods on Land for information.



15. REGULATORY INFORMATION

Country/ Region: New Zealand
Inventory: NZ Inventory of Chemicals
Status: Listed

EPA New Zealand HSNO Approval Code: HSR002652; Solvent (Flammable, Toxic [6.7]) Group Standard 2006.

Refer www.epa.govt.nz for information on Controls.

16. OTHER INFORMATION

Issue: 4
Date of Issue: 29th March 2024
Reasons for Issue: 5-year review of Safety Data Sheet.
Replaces: 29th March 2019

Abbreviations:

CAS No	Chemical Abstracts Number
EPA	Environmental Risk Management Authority
HSNO	Hazardous Substances and New Organisms
NZIoC	New Zealand Inventory of Chemicals
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
WES	Workplace Exposure Standard

References:

Supplier Safety Data Sheets
EPA website: www.epa.govt.nz

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact Supreme Cleaning Products.

END OF SAFETY DATA SHEET