

Safety Data Sheet

Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Airomist PRO 6000 Aerosol Air Freshener

Uses: Air freshener aerosol.

Company: Ardrich Limited

Address: 31 Hannigan Drive, St Johns, Auckland 1072

Telephone: +64 9 570 2861

Email: info@ardrich.net

Emergency Number: +64 9 570 2861

National Poison Centre: 0800 764 766 (0800 POISON)

Section 2 – HAZARDS IDENTIFICATION

Product is classified as hazardous according to Schedules 1 to 6 of the *Hazardous Substance (Minimum Degrees of Hazard) Regulations 2001* of the HSNO Act, 1996.

HSNO Classifications:

2.1.2A	Extremely flammable aerosol
6.1E (oral)	Acutely toxic
6.3A	Irritating to the skin
6.4A	Irritating to the eye
9.1A	Very ecotoxic in the aquatic environment (fish, crustacean, algal)
9.3C	Harmful to terrestrial vertebrates



Signal Words: Warning

Hazard Statements

H222	Extremely flammable aerosol.
H303	May be harmful if swallowed.
H315	Causes skin irritation.
H400	Very toxic to aquatic life.
H433	Harmful to terrestrial vertebrates.

Precaution Statements

P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat and open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P410, P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Ethanol Denatured	64-17-5	0 - 10
Lauryl Methacrylate	142-90-5	0 - 10
Phenol, 5-chloro-2-(2,4-dichlorophenoxy)-	3380-34-5	0 - 10
Hydrocarbon propellant (Propane, Butane)	106-97-8, 74-98-6	> 60
Other ingredients determined to not be hazardous	-	to 100%

Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTER or doctor.

Eye contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Inhalation:	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician.
Ingestion:	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Where there is risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs. Obtain immediate medical attention.
Skin contact:	Direct contact may cause irritation in sensitive individuals. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/ attention.
Notes to physician:	Treat symptomatically and supportively. Risk of aspiration to lungs. No specific antidote. Potential for chemical pneumonitis. Consider: gastric lavage with protected airway, administration of activated charcoal.

Section 5 – FIRE-FIGHTING MEASURES

Specific hazards:	Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. Will float and can be re-ignited on surface water. Will burn if involved in a fire.
Further advice:	On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion. Use water spray to keep fire-exposed containers cool.
Extinguishing media:	For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment. Do NOT use straight streams of water.
Hazchem Code:	2YE

Section 6 – ACCIDENTAL RELEASE MEASURES

Minor spills:	Clean up immediately. Remove all sources of ignition. If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Provide ventilation. Wash with water.
Major spills:	Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal. Wash area down with excess water.
Disposal Statement	Product wastes are consider ecotoxic and should be disposed of in accordance with local legislation. Incineration is suggested. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with local legislation.

Section 7 – HANDLING AND STORAGE

Handling Precautions: Read product label before use. This product is highly flammable. Do not use near open flame, or sources of ignition. No smoking. Pressurized container: Do not pierce or burn, even after use.

Use outdoors or in well-ventilated area. Wear personal protective equipment. Wash hands with soap and water after handling. Wash protective clothing separate to household laundry.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.

Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits: No value assigned for this specific material. However, exposure standards for constituents;

Material	TWA, mg/m ³	STEL, mg/m ³	Category/Notices
Ethanol Denatured	1880	-	-
Butane	1900	-	-
Propane	Simple Asphyxiant	-	-

Additional Information: Wash hands before eating, drinking and smoking. Do not eat, drink or smoke when using this product.

Engineering Controls: No controls required when handling small quantities. Use with adequate ventilation.

Larger quantities: General exhaust is adequate under normal operating conditions. Ventilation equipment should be explosion-resistant.

Protective Equipment: Gloves, safety glasses or chemical goggles are recommended in an industrial environment. If TWA is exceeded, wear an approved respirator with a type A filter.

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Transparent volatile liquid with a mild odour.

pH: Not applicable.

Vapour Density: > 1 (Air =1)

Vapour Pressure, kPa: 300 - 600

Boiling Point, °C: Not applicable.

Melting Point, °C: Not applicable.

Specific Gravity: Not applicable.

Flash Point, °C: < 0

Explosion Limit, % v/v: LEL 1.2% UEL 9.5%

Autoignition Temp, °C: Not applicable.

Solubility: Miscible in water. Soluble in common organic solvents.

Section 10 – STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use and storage. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

Section 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment: Information given is based on product testing, and/or similar products, and/or components.

Acute Oral Toxicity: Low toxicity: LD50 calculated to be > 5000 mg/kg, Rat. Harmful if swallowed.

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis.

Acute Dermal Toxicity: Low toxicity: LD50 estimated to be >5000 mg/kg, Rabbit.

Acute Inhalation Toxicity: High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

Skin Irritation:	May cause mild skin irritation. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.
Eye Irritation:	Vapours may be irritating to the eye.
Respiratory Irritation:	Inhalation of vapours or mists may cause irritation to the respiratory system.
Repeated Dose Toxicity:	Central nervous system: repeated exposure affects the nervous system. May cause damage to organs. Prolonged contact with product may result in irritant contact dermatitis.
Additional Information:	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

Section 12 – ECOTOXICITY INFORMATION

Ecotoxicity:	Very toxic in aquatic environments. Harmful to terrestrial vertebrates.
Bioaccumulation:	Has the potential to bioaccumulate.

Section 13 – DISPOSAL CONSIDERATIONS

Material Disposal:	Product wastes are consider ecotoxic and should be disposed of applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water.
Container Disposal:	Pressurized container: Do not pierce or burn, even after use. Recycle empty container if possible. Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

Section 14 – TRANSPORT INFORMATION

Transport:	Classified as a dangerous goods according to the NZ Land Transport Rule for road and rail, IMDG for sea, IATA for air. Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7. They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.
Proper Shipping Name:	Aerosols
UN Number:	1950
Dangerous Goods Class:	2.1 Flammable aerosols
Subsidiary Risk:	Class 6 Toxic, Class 9 Ecotoxic.
Packing Group:	Not applicable
Hazchem Code:	2YE

Section 15 – REGULATORY INFORMATION

EPA NZ Group Standard Classification: Aerosols (Subsidiary Hazard) Group Standard HSR002519

Section 16 – OTHER INFORMATION

This MSDS summarises our best knowledge of the health and safety hazard information. Since we cannot control the conditions under which the product may be used, each user must review this MSDS in the context of how the user intends to use the product.

End of msds.